

1416340

https://www.phoenixcontact.com/us/products/1416340

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector, rear mounting, 8-position-SPEEDCON, coding: A , on free cable end, Rear mounting, Individual wires, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1239114

Commercial data

| Item number | 1416340 |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Sales key | AB24 |
| Product key | ABQCHB |
| GTIN | 4055626071916 |
| Weight per piece (including packing) | 55.4 g |
| Weight per piece (excluding packing) | 55.4 g |
| Customs tariff number | 85444290 |
| Country of origin | DE |



1416340

https://www.phoenixcontact.com/us/products/1416340

Technical data

General

Notes

| Мс | nting | |
|----|-------------------|------------------|
| | Mounting type | Rear mounting |
| | Connection method | Individual wires |

Lock nut is included in the scope of delivery

Product properties

| Product type | Circular connectors (device side) |
|---------------------|-----------------------------------|
| Number of positions | 8 |
| Coding | A |
| Thread type | M12 |

Connection data

Conductor connection

| Connection method | Individual wires |
|-------------------------|------------------|
| Contact connection type | Socket |

Connector

Connection 2

| Head design | free cable end |
|-------------|----------------|
|-------------|----------------|



1416340

https://www.phoenixcontact.com/us/products/1416340

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1416340

| UL Recognized Approval ID: E118976-20100522 | | | | | |
|--|--|--------------------------------|--------------------------------|-------------------|-------------------------------|
| | | Nominal voltage U _N | Nominal current I _N | Cross section AWG | Cross section mm ² |
| | | 30 V | 2 A | - 24 | - |

| EHC | EAC |
|------|----------------------|
| LIIL | Approval ID: B.01687 |

| c 911 vs | cULus Recognized Approval ID: E221474-20140616 | | | | |
|-----------------|--|--------------------------------|--------------------------------|-------------------|-------------------------------|
| | | Nominal voltage U _N | Nominal current I _N | Cross section AWG | Cross section mm ² |
| | | 30 V | 2 A | 24 - 22 | - |



1416340

https://www.phoenixcontact.com/us/products/1416340

Classifications

ECLASS

| | ECLASS-11.0 | 27440103 | |
|--------|-------------|----------|--|
| | ECLASS-12.0 | 27440103 | |
| | ECLASS-13.0 | 27440103 | |
| | | | |
| ETIM | | | |
| | ETIM 8.0 | EC003570 | |
| UNSPSC | | | |
| | UNSPSC 21.0 | 39121400 | |



1416340

https://www.phoenixcontact.com/us/products/1416340

Environmental product compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|--|
| | |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com