








APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/26/21	



**SPECIFICATIONS:**




Material:  
 Case: DAP, Rated UL94V-0  
 Plunger: Brass, color Black w/ O-Ring  
 Bushing: Brass, color Black w/ O-Ring  
 Movable Contact: Copper Alloy, Silver Plated  
 Terminal: Copper Alloy, Silver Plated

Electrical:  
 Rating: 6A @ 125VAC or 28V DC  
 3A @ 250VAC

Contact resistance: 10 mΩ max  
 Insulation resistance: 1,000 Mohms min  
 Dielectric withstanding voltage: 1,500V RMS @Sea level  
 Life: 50,000 cycles at full load  
 Temperature Rating:  
 Operating temperature: -30°C to +85°C

Environmental:

Sealed IP68 Rated  
 Lead free, RoHS compliant



BUTTON POSITION		
FUNCTION	ON	ON
TERMINALS	2-3	2-1

UNLESS OTHERWISE SPECIFIED  
 ALL DIMENSIONS ARE INCHES [MM]  
 TOLERANCES: EXCEPT AS NOTED

.X	± .10	∅.X	± .10
.XX	± .020	∅.XX	± .015
.XXX	± .015	∅.XXX	± .010

APPROVALS		DATE
DRAWN	LH	1/26/21
CHECKED	AC	1/26/21
APPROVED		

**ADAM TECH** 909 Rahway Avenue,  
 Union, NJ 07083  
 Phone: 908-687-5000  
 Fax: 908-687-5710

TITLE: HIGH PERFORMANCE PUSH BUTTON SWITCH,  
 SPDT, ON-ON, SILVER PLATED, PCB TAILS

SIZE	PART NO.	REV.
X	SW-PB10-AAA2QE-4	-

REF: S00198T SCALE: NTS SHEET 1 OF 1