# BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

#### ATS-52270P-C1-R0

27.00 x 27.00 x 17.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type:maxiFLOWHeat Sink Attachment:Thermal TapeEquivalent Part Number:ATS-52270P-C2-R0

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- maxiFLOW<sup>™</sup> design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

### **Thermal Performance**

|                    |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 3.7 °C/W            | 3 °C/W              | 2.6 °C/W            | 2.3 °C/W            | 2.1 °C/W            | 2 °C/W              | 1.9 °C/W            |
|                    | Ducted Flow   | 2.9                 | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 |

## **Product Detail**

| Schematic Image                                | Dimension A   | Dimension B   | Dimension C   | Dimension D   | ТІМ                               | Finish                            |
|--|---|---|---|---|-----------------------------------|-----------------------------------|
|  | 27.00 mm  | 27.00 mm  | 17.50 mm  | 48.36 mm  | T412                              | BLUE-ANODIZED                     |
|  | <ul> <li>Dimension</li> <li>ATS-5227<br/>(Saint-Gol</li> <li>Thermal p<br/>application</li> <li>ATS resen<br/>performan</li> <li>ATS certifi</li> </ul> | OP-C2-R0 is the exa<br>bain C675).<br>erformance data are<br>n.<br>ves the right to upda<br>ce.<br>ies that this heat sin | imponent size.<br>leight from the bottor<br>act heat sink assemb<br>e provided for referer<br>ate or change its prod<br>k assembly is RoHS<br>lstom options availab | ly with an equivalen<br>nce only. Actual perf<br>ducts without notice<br>-6 and REACH com | t thermal<br>ormance<br>to improv | interface material<br>may vary by |
| *Image above is for illustration purpose only. |   |   |   |   |                                   |                                   |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

