


CK2,5-ED-2,50ST AG

Order No.: 1663611

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663611>Turned 2.5 crimp contact, individual male contact, core diameter 2.5 mm², silver-plated**Commercial data**

| | |
|--------------------------|--|
| GTIN (EAN) |  |
| sales group | D090 |
| Pack | 100 pcs. |
| Customs tariff | 74152900 |
| Catalog page information | Page 528 (PC-2009) |

Product notesWEEE/RoHS-compliant since:
12/01/2005

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Electrical characteristics**

| | |
|---------------------------------|--|
| Note | for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers, the quality of a crimp connection is determined by the DIN EN 60 352-2 |
| Volume resistance | $\leq 0.003 \Omega$ |
| Ambient temperature (operation) | -40 °C ... 125 °C |

Mechanical characteristics

| | |
|---|-------------------------------|
| Conductor cross-section | 2.5 mm ² |
| Connection cross-section AWG | 14 |
| Stripping length of the individual wire | 7.5 mm (9.5 mm at HC-M-HV...) |
| Insertion/withdrawal cycles | ≥ 500 |

General characteristics

| | |
|-------------------|---|
| Type | Individual male contact |
| Connection method | Crimp connection |
| Connection | for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers. The quality of a crimp connection is determined by the DIN EN 60 352-2. |

Material data

| | |
|--------------------------|--------------------|
| Contact material | Copper alloy |
| Contact surface material | hard-silver plated |

Certificates / Approvals



Certification GOST, UL

Accessories


| Item | Designation | Description |
|------|-------------|-------------|
|------|-------------|-------------|

Tools

| | | |
|---------|-------------------------|--|
| 1676734 | CK1,6/2,5-MWZ | Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections |
| 1662722 | CK2,5-EWZ | Contact removal tool, for turned and rolled CK- 2.5-... contacts |
| 1687419 | CRIMPFOX-1,6/2,5-ED-4,0 | Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED... |

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;