

HDC enclosures HDC IP68 16B TOS 1PG29

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMC-resistant.

General ordering data

Order No.	<u>1082760000</u>
Туре	HDC IP68 16B TOS 1PG29
Version	HDC enclosures, Size: 6, Protection degree: IP 68, Plug housing, Screw plug, Standard, Size of cable entries: PG 29
GTIN (EAN)	4032248846245
Qty.	1 pc(s).



HDC enclosures HDC IP68 16B TOS 1PG29

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

ROHS

Dimensions and weights			
Net weight	125 g		
- Worgilt	123 y		
Temperatures			
Continuous an autimortana main	-50 °C	Continue of the state of the st	125 °C
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	125 °C
Dimensions			
Total length housing	110.5 mm	Width housing C	58 mm
Height of housing B	164 mm	Cable entry	w. threading
General data			
Harring made material	dia anna alumainium		
Housing main material	diecast aluminium		
Version			
Design of housing	Plug housing	Size	6
Design	Standard	Top part/bottom part/lid	upper part
Design of locking system	Screw plug	Cable entry	w. threading
Size of cable entries	PG 29	Number of cable entry on top	1
Number of cable entry sideways	0		
Classifications			
eClass 6.2	27-14-34-19	eClass 7.1	27-44-05-15
eClass 0.2	Z1-14-34-19	eCiass /. I	Z /-44-UD-15
Approvals			
Approvals	CT CT		

Conform



HDC enclosures HDC IP68 16B TOS 1PG29

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

