

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073



Features:

- Frequency:
824-894/1710-2170MHz or
880-960/1710-2170MHz
- Size 10 x 3.2 x 4 mm
- PCB Keep out 40 x 10 mm
- Polarization Linear
- Radiation pattern Omni

Applications:

- 2G/3G
- Nb-IoT
- GSM850 or EGSM900/
PCN1800, PCS1900 and
WCDMA

All dimensions are in mm / inches

Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

For more information:

Pulse Worldwide Headquarters
15255 Innovation Drive #100
San Diego, CA 92128
USA
Tel: 1-858-674-8100

Pulse/Larsen Antennas
18110 SE 34th St Bldg 2 Suite 250
Vancouver, WA 98683
USA
Tel: 1-360-944-7551

Europe Headquarters
Pulse GmbH & Do, KG
Zeppelinstrasse 15
Herrenberg, Germany
Tel: 49 7032 7806 0

Pulse (Suzhou) Wireless Products Co, Inc.
99 Huo Ju Road(#29 Bldg, 4th Phase
Suzhou New District
Jiangsu Province, Suzhou 215009 PR China
Tel: 86 512 6807 9998



Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

ELECTRICAL SPECIFICATIONS

Antenna Type	Chip antenna
Frequency	Version1: 868-870MHz 1710-2170MHz Version2: 880-960MHz 1710-2170MHz
Nominal Impedance	50 Ω
Radiation Pattern	Omni
Polarization	Vertical
Power Withstanding	3W

MECHANICAL SPECIFICATIONS

Compact size	10 x 3.2 x 4mm
Weight	0.6g
Fixing system	SMT
MSL(MOISTURE SENSITIVITY LEVEL)	1

ENVIRONMENTAL SPECIFICATIONS


Operating Temperature	-40 ~ +85° C
Storage Temperature	-10 ~ +30° C
RoHS Compliant	Yes

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

MECHANICAL DRAWING



No.	Terminal Name	Terminal Dimensions
1	Feed	1.5 x 2.75 mm
2	Support pad	1.5 x 2.75 mm
Antenna is symmetrical and orientation on footprint can be rotated 180 degrees without change in performance		

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

PWB Layout


Test Setup for Electrical Measurements

Recommended test board- layout for electrical characteristic measurement. Test board outline size 105 x 40mm. Ground cleared under antenna 40mm x 10mm.

Version 1: GSM850, PCN1800, PCS1900 and WCDMA I

All metallization should be removed from all PWB layers on ground clearance area (10.00 x 40.00 mm)


Ground Clearance Area (10.00mm x 40.00mm)




GSM850 frequency tuning area
PWB layout depends on application and surrounding mechanics / materials.

W3073 Ceramic chip antenna location


Layout in Top Copper



Layout in Bottom Copper



Stub for PCN1800, PCS1900 and WCDMA I frequency tuning
Length depends on application and surrounding mechanics / materials.



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.
CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna



Series: Ceramic Chip Antenna

PART NUMBER: W3073



PWB Layout

Version 2: EGSM900, PCN1800, PCS1900 and WCDMA I

Layout in Top Copper



Layout in Bottom Copper



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.


Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073


3D- view of Test Setup

Version 1: GSM850, PCN1800, PCS1900 and WCDMA I



3D- view of Test Setup

Version 2: EGSM900, PCN1800, PCS1900 and WCDMA I



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION



This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

GHARTS



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION



This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

CHARTS



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.





Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

CHARTS



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.



Description: Quad Band Monopole Ceramic Chip Antenna


Series: Ceramic Chip Antenna

PART NUMBER: W3073


CHARTS

Version 1: Typical Free Space Radiation Patterns



ZX Plane



XY Plane



YZ Plane



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna


Series: Ceramic Chip Antenna

PART NUMBER: W3073

CHARTS

Version 1: Typical Free Space Radiation Patterns

ZX Plane




1710MHz
Avg(dBi) = -4.76
Peak(dBi) = -0.74
Avg -3(deg) = 105.5

1990MHz
Avg (dBi) = -2.70
Peak (dBi) = 1.52
Avg -3 (deg) = 71.5

2170MHz
Avg (dBi) = -4.37
Peak (dBi) = -0.26
Avg -3 (deg) = 66.5

— 1710MHz — 1990MHz — 2170MHz

XY Plane




1710MHz
Avg(dBi) = -4.59
Peak(dBi) = -1.74
Avg -3(deg) = 181.5

1990MHz
Avg (dBi) = -3.90
Peak (dBi) = -1.18
Avg -3 (deg) = 189.5

2170MHz
Avg (dBi) = -6.49
Peak (dBi) = -3.85
Avg -3 (deg) = 221.5

— 1710MHz — 1990MHz — 2170MHz

YZ Plane




1710MHz
Avg(dBi) = -6.15
Peak(dBi) = -1.11
Avg -3(deg) = 68.5

1990MHz
Avg (dBi) = -3.90
Peak (dBi) = 0.35
Avg -3 (deg) = 84.5

2170MHz
Avg (dBi) = -5.42
Peak (dBi) = -1.54
Avg -3 (deg) = 104.5

— 1710MHz — 1990MHz — 2170MHz



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna


Series: Ceramic Chip Antenna

PART NUMBER: W3073


CHARTS

Version 2: Typical Free Space Radiation Patterns



ZX Plane



XY Plane



YZ Plane



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna


Series: Ceramic Chip Antenna

PART NUMBER: W3073


CHARTS

Version 2: Typical Free Space Radiation Patterns



ZX Plane



XY Plane



YZ Plane



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

Recommendations for ceramic chip antenna storage

Storage time

Products should be used within 6 months from the day of manufacturers packaging even when they are stored under below mentioned conditions. Longer storage period may decrease the component solderability.

Storage environmental conditions

To maintain solderability of Pulse ceramic products care must be taken to control the storage and use conditions:

- Do not store or use products in a corrosive atmosphere, especially where chloride, sulphur or sulfide, alkali or acid salts exist in the air. Corrosive gases may cause oxidation of electrodes and reduce solderability
- Keep temperature and humidity stable and do not exceed the below mentioned minimum and maximum conditions: Temperature: -10 to +30 Deg C
Humidity: below 60% RH
- Do not store the products under direct sun light.

It is recommended to keep the products in manufacturers packing (tape&reel) until the time of assembly and soldering process. Air tight vacuum package is recommended in the conditions where it is know to be some corrosive gases.

Handling

Do not touch the components with bare hands. Protective gloves must be used to prevent contamination of terminals which may cause reduced solderability. Do not touch or damage the silver plated surface by any sharp objects. Soft materials (plastic, wood etc.) must be used if tweezers or other tools are used to pick the components. Avoid any excess mechanical shock or vibration during storage and handling.

Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

Recommendation for reflow soldering process

Printing stencil thickness 0,15 - 0,25 mm is recommended for the solder paste. The maximum soldering temperature should not exceed 260°C. The temperature profile recommendations for reflow soldering process is presented in the Figures 1 and 2. The reflow profile

presented in figure 1 describes minimum reflow temperatures. The reflow profile presented in figure 2 describes maximum reflow temperatures. located at the center of the coverage area.

	Method of heat transfer	Controlled hot air convection
1	Average temperature gradient in preheating	2.5 °C/s
2	Soak time	2-3 minutes
3	Max temperature gradient in reflow	3 °C/s
4	Time above 217 °C	Max 30 sec
5	Peak temperature in reflow	230 °C for 10 seconds
6	Temperature gradient in cooling	Max -5 °C/s




Figure 1. Minimum temperature profile recommendation for reflow soldering process

Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.


Description: Quad Band Monopole Ceramic Chip Antenna

Series: Ceramic Chip Antenna

PART NUMBER: W3073

Recommendation for reflow soldering process

	Method of heat transfer	Controlled hot air convection
1	Average temperature gradient in preheating	2.5 °C/s
2	Soak time	2-3 minutes
3	Max temperature gradient in reflow	3 °C/s
4	Time above 217 °C	Max 60 sec
5	Time above 230 °C	Max 50 sec
6	Time above 250 °C	Max 10 sec
7	Peak temperature in reflow	260 °C for 5 seconds
8	Temperature gradient in cooling	Max -5 °C/s



Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

Description: Quad Band Monopole Ceramic Chip Antenna


Series: Ceramic Chip Antenna

PART NUMBER: W3073

PACKAGING

Packing form

**500pcs in one Reel,
3 reel in one inbox (1500 pcs),
2 inbox in out box (3000pcs)**




CARRIER TAPE H85-00158
width=24,00 depth=4.15
COVER TAPE H85-00159
width=21.20



LENGTH OF TAPE:

- Leader section: min 350 mm before component section
- Trailer section: min 40 mm after component section.

Empty part cavities at leader and trailer section of the tape must be sealed with top cover tape.



BOX H85-00128 (182x182x125)	1 pcs
- LABEL	1 pcs/BOX
REEL H85-00160 (D180,W28)	4 pcs
- REEL LABEL	1 pcs/REEL

MATERIAL					
HANDLINGS					
		RATIO	DRWN	160107 PeHa	H
			DGNER		G
			CHKD		F
			APPRD		E
PRODUCT		H90-OY800-F01P01		APPRD BY	D
DENOMINATION		PACKING FORM			C
					B
					A
		VERSION		MOD/DATE/NAME	

Issue: 2037

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

