

Senseair Sunrise HVAC

A new generation NDIR sensor

Senseair Sunrise HVAC is a new generation NDIR sensor with Optical Solid State design. Electronics with no moving parts makes this sensor robust and resistant to vibrations. Any application with a tough environment or in environments with explosion risk is benefited by the solid state design.

It is the first NDIR sensor with LED technology that truly saves power while maintaining a high precision.

The ultra low power consumption makes Sunrise optimal for battery and wireless applications.

The sensor has an accuracy (CO₂) ±30 ppm ±3% of reading. Thanks to the built-in self-correcting algorithm you can mount and forget your sensor for the next 15 years and it will still be accurate.



Standard specification

Article No.	006-0-0008
Measured gas	Carbon dioxide (CO ₂)
Operating principle	Non-dispersive infrared
Measurement range (CO ₂)	400 – 5000 ppm; extended range up to 10000 ppm
Accuracy (CO ₂)	±30 ppm ±3% of reading ^{1,2} (extended range ±10% of reading)
Average current, typical	See table to the right
Measurement period	Default: 16 s, 8 samples (adjustable by host)
Steady state current during sampling	90 mA
Peak current	<125 mA
Power supply	3.05 – 5.5 V
Dimensions	33.5 x 19.7 x 11.5 mm
Weight	5 g
Life expectancy	>15 years
Operating range	0 – 50 °C, 0 – 85% RH
Storage temperature	-40 – 70 °C
Serial communication	UART, I ² C

Key benefits

- Optical Solid State
- Ultra Low Power consumption
- Compliant with ANSI/ASHRAE Standard 62.1-2022
- Compliant with RESET grad B
- Compliant with WELL Building Standard® (WELL v2™)
- High Precision
- Robust
- Mass Production
- Self-correcting

Average current (typical), at continuous and single measurement mode respectively

Measurement period	2 Samples		8 Samples		32 Samples	
	Cont	Single	Cont	Single	Cont	Single
16 s	22 µA		34 µA			
1 min	18 µA	7 µA	21 µA	17 µA	35 µA	27 µA
5 min	16 µA	1 µA	17 µA	3 µA	20 µA	5 µA

Note 1: 15 – 35 °C, 0 – 80% RH, after 3 ABC periods and default measurements settings.
Note 2: Specification is referenced to uncertainty of calibration gas mixtures (±1%).
Note 3: Unprotected against surges and reverse power supply polarity.



Senseair