

ZB4BC180

Head for push button, Harmony XB4,
pushbutton harsh environment, white, without
marking



Main

| | |
|-------------------------------|-----------------------|
| Range of Product | Harmony XB4 |
| Product or Component Type | Head for push-button |
| Device short name | ZB4 |
| Bezel material | Chromium plated metal |
| Head type | Standard |
| Mounting diameter | 0.87 in (22 mm) |
| Sale per indivisible quantity | 1 |

Complementary

| | |
|-----------------------------------|---|
| CAD overall width | 1.46 in (37 mm) |
| CAD overall height | 0.73 in (18.5 mm) |
| CAD overall depth | 1.46 in (37 mm) |
| Net Weight | 0.08 lb(US) (0.036 kg) |
| Electrical shock protection class | Class I IEC 61140 |
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | White flush, unmarked |
| Operator additional information | Vertical mounting Horizontal mounting |
| Mechanical durability | 10000000 cycles |
| Vibration resistance | 5 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 |
| Main group | Harsh environment |
| Group of product | Flush unmarked |
| Cap/operator or lens colour | White |
| Marking | Unmarked |
| Electrical composition code | C1 9 single front mounting C2 9 single and double front mounting C11 3 single front mounting C15 1 single front mounting |
| Device presentation | Basic element |

Environment

| | |
|---------------------------------------|---|
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |
| Ambient Air Temperature for Operation | -40...158 °F (-40...70 °C) |
| IP degree of protection | IP66 IEC 60529 IP69K IP67 IP69 |
| NEMA degree of protection | NEMA 4 UL 508 NEMA 13 NEMA 12 |
| Resistance to high pressure washer | 0.01 psi (90 Pa) 180 °F (82.5 °C) |
| IK degree of protection | IK06 IEC 62262 |

| | |
|------------------------|---|
| Standards | IEC 60947-1 IEC 60947-5-1 CSA C22.2 UL 508 |
| Product Certifications | UL CSA CE |

Ordering and shipping details

| | |
|-----------------------|-----------------------------------|
| Category | 22468-PUSHBUTTONS,22MM(METAL) NEW |
| Discount Schedule | CS2 |
| GTIN | 3606480444098 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.20 oz (34.0 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.48 in (3.76 cm) |
| Package 1 width | 1.46 in (3.7 cm) |
| Package 1 Length | 1.46 in (3.7 cm) |


Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty


| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions




Installation on Flat Surface

Without Protective Guard




(1) $\varnothing 22.5$ mm recommended ($\varnothing 22.3_0^{+0.4}$) / $\varnothing 0.89$ in. recommended ($\varnothing 0.88_0^{+0.016}$)

With Protective Guard



(1) $\varnothing 22.5$ mm recommended ($\varnothing 22.3_0^{+0.4}$) / $\varnothing 0.89$ in. recommended ($\varnothing 0.88_0^{+0.016}$)

Electrical Composition Corresponding to Code C1



Electrical Composition Corresponding to Code C2




Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1




Electrical Composition Corresponding to Code C15


1 N/O



1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



Legend

Single contact



Double contact



Light block



Possible location

