Mounting carrier; 3-pole; for sockets and plugs; Plastic; gray





Color
Color:

 $\label{lem:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-303



Item description

Mounting accessories WINSTA® MINI 3-pole

Realize the energy supply with ease: The mounting accessories from the *WINSTA*® MINI product line is the product of your choice for error-free electrical installation. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too. Due to its particularly minimal dimensions, our *WINSTA*® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is very suitable in very restricted spaces, i.e., for connections when very little room is available.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is ideally tailored to the strict requirements of building installation. It makes electrical installation pluggable, and thus faster, more reliable, and error-free. Use of this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Take advantage of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with protection against mismating from WAGO.

- consistent IP40 protection
- quick replacement of defective units during ongoing operation

Data

Connection data

Connection 1

Pole number 3

Mechanical Data

Suitable for socket and plug

Material Data

Note (material data)

Information on material specifications can be found here

Color gray

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-303



Insulation material	Polyamide (PA66)
Flammability class per UL94	VO
Fire load	0.017 MJ
Weight	0.6 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (50) pcs
Packaging type	box
Country of origin	DE
GTIN	4055143838610
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status Co	ompliant,No Exemption
---------------------------	-----------------------

Downloads

Documentation

Bid Text

890-303 X81 - Datei	2019 年2月19日	xml 2.7 kB	Download
890-303 doc - Datei	2015 年3月16日	doc 24.1 kB	Download

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-303



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-303

Mounting carrier; 3-pole; for sockets and plugs; Plastic; gray

URL

Download

Installation Notes

Product family

WINSTA® MINI

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.