

6

5

4




3

2


1

PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300480170	E11A06310M010	3' 3" +2.19'/-0' [1M +55.6/-0 mm]
1300480172	E11A06310M050	16' 4" +6.5'/-0' [5M +165.0/-0 mm]


AUX VIEW
SCALE 1:4



MALE- FACE VIEW



WIRING DIAGRAM



MALE- FACE VIEW

NOTES:

- 1) MATERIAL: SEE TABLE
- 2) FINISHES: SEE TABLE
- 3) CABLE: #22/4 SHIELDED PUR
- 4) ELECTRICAL DATA:
ACCORDING TO CAT5e ETHERNET STANDARD
MAX. VOLTAGE: 30V
MAX. CURRENT 1.5A
- 5) ENVIRONMENTAL:
PROTECTION IP67
TEMPERATURE RANGE: -20°C TO 75°C
- 6) WRAP LABEL IS MARKED WITH P/N, DATE CODE,
VOLTAGE & AMPERAGE.
- 7) ASSEMBLY IS RoHS COMPLIANT.

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
6	1	LABEL	PLASTIC FILM	BLACK/YELLOW
5	2	INSERT	PUR	BLACK
4	8	PIN CONTACT	COPPER ALLOY	GOLD PLATED
3	2	M12 COUPLING NUT	BRASS	NICKEL
2	2	OVERMOLD	PUR	BLACK
1	1	ETHERNET CABLE-CAT5E	PUR JACKET	TEAL

SD RELEASE
EC NO: WEL2010-0005
7/13/09
DRWN: VOU
CHKD: BWOODMAN
APPR: JFMURPHY 2009/07/20

QUALITY SYMBOLS
▽=0
▽C=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±----	±----
3 PLACES	±----	±.005
2 PLACES	±----	±.010
1 PLACE	±----	±.020

ANGULAR ± 1/2°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM

DRAWN BY DATE
VOU 2009/07/06
CHECKED BY DATE
BWOODMAN 2009/07/31
APPROVED BY DATE

SCALE
3:4DESIGN UNITS
INCH

THIRD ANGLE
PROJECTION

TITLE
MICRO-CHANGE CABLE ASSY
4P M/MP 90/90 D-CODE
#22/4 SHIELDED PUR

molex MOLEX INCORPORATED

MATERIAL NO.
SEE CHART

DOCUMENT NO.
SD-120108-025

SHEET NO.
1 OF 1

SIZE
A

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

6

5

4

3

2

1