



Defoamer DF1

Product# 1555

Product Description

Reduce foaming as cleaner becomes loaded to extend bath life. Add directly to sump at 1 to 4 fl. oz. (30-120ml) per 100 gallons (379L). Dilute in spray bottle to 15% with DI water to eliminate foaming issue on the spot.

Features / Benefits

- Effective at all processing temperatures
- Extends bath life
- Silicone & particulate free
- Nonflammable

Applications

Reduce foaming common with water-based cleaners used in...

- Inline defluxing equipment
- Batch defluxing equipment
- Spray-in-air batch stencil cleaning equipment
- Submersion batch stencil cleaning equipment

About TECHSPRAY RENEW™

TECHSPRAY RENEW™ is a brand that represents **High Performance Eco-Cleaning™**. Techspray® has applied our expertise in solvent cleaning to formulate some of the most effective eco-friendly cleaners on the market. Performance is our top priority, using the best “green” solutions as they become available. We all are at the cusp of the ongoing movement toward sustainable products, packaging, and processes. It is Techspray’s intention to stay at the cutting-edge while keeping our products powerful and cost effective.

Compatibility

Defoamer DF1 is compatible within normal operating conditions of in-line and batch (spray- in-air) cleaning and with exposed materials normally found within respective equipment.

Packaging and Availability

1555-P 1 pt. (473mL) container

Chemical Properties

| | |
|-------------|--------------------------------|
| Flash Point | >100°C |
| Density | 212°F (100°C) |
| VOC (EPA) | 91% |
| SHELF LIFE: | 5 years unopened, 2 years open |

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray’s only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



● **North America**
 Techspray®
 8125 Cobb Center Drive
 Kennesaw, GA 30152
 800-858-4043
tsales@techspray.com

● **Europe**
 ITW Contamination Control BV
 Saffierlaan 5, 2132 VZ Hoofddorp
 The Netherlands
 +31 88 1307 400
info@itw-cc.com

● **Countries outside the US**
 Call to locate a distributor in your country