BodyCom[™] Technology


Summary

Microchip's BodyCom Technology is a short-range, low-datarate communication solution for securely connecting to a wide range of wireless applications.

Compared to other existing wireless technologies BodyCom Technology offers lower active and standby energy usage, increases security through bidirectional authentication, provides a secure communication channel using the human body and allows for simpler circuit-level designs.

How Does BodyCom Technology Work?

Activated by capacitively coupling to the human body, the system communicates bidirectionally between a centralized controller and one or more wireless mobile units. Intra-body communication takes place using the human body as the transmission medium.



Applications

- Access control
 - Passive Keyless Entry (PKE)
 - Security systems
 - Home/industrial door locks
 - Pet doors
- Personal safety & security
 - Equipment access/disable
 - Power Tools
 - Firearms
 - Computer systems

- Medical
 - Patient monitoring
 - Hospital room access
 - Equipment tracking
- Consumer
 - Profile Management for gaming consoles
 - Exercise equipment



Benefits

- Simpler implementation
 - No RF antenna design necessary
 - Low-frequency design using common microcontroller and AFE frequencies (125 kHz/8 MHz), no external crystals needed
 - · Complies with FCC Part 15-B, Radiated Emissions
 - Lower overall BOM, compared to existing technologies
- Lower power consumption
 - No wireless transceiver required for two-way communication
 - Not using high-power inductive fields
- More secure communication channel
 - Provides bidirectional authentication through the human body
 - Prevents the "Relay Attack" problem typical in PKE solutions
- Supports advanced encryption solutions
 - Such as KEELog® Technology with AES-128



Development Support



BodyCom™ Development Ki (Part # DM160213)

- Free BodyCom Technology Development V1.0 Framework supplied via free software libraries for all PIC[®] MCUs
 - BodyCom Technology communication library
 - · Application code examples
 - PC development GUI
- BodyCom Technology Development Kit (DM160213)
 - · Central controller unit + two wireless mobile units

Applications Notes and Data Sheets

- AN1391: Introduction to the BodyCom Technology
- DS41391: PIC16F/LF1826/27, 18/20/28-Pin Flash Microcontrollers with nanoWatt XLP Technology
- DS22304: MCP2035 Analog Front-End Device for BodyCom Technology Applications



www.microchip.com/bodycom

Visit our web site for additional product information and to locate your local sales office.

Microchip Technology Inc. • 2355 W. Chandler Blvd. • Chandler, AZ 85224-6199

Microcontrollers • Digital Signal Controllers • Analog • Memory • Wireless

Information subject to change. The Microchip name and logo, the Microchip logo, dsPIC, PIC are registered trademarks and MiWi, PICtail and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks mentioned herein are property of their respective companies. © 2013, Microchip Technology Incorporated. All Rights Reserved. 2/13 DS30685A