

# PCM Series Ultraminiature Surface Mount Slide Switches



## Features/Benefits

- Ultraminiature surface mount
- Low profile
- SPDT & SP3T models
- RoHS compliant

## Typical Applications

- Computer peripherals & network products
- Telecommunication products
- Test & measurement equipment

## Specifications

CONTACT RATING: 0.3A @ 6 VDC.  
 ELECTRICAL LIFE: 10,000 cycles.  
 CONTACT RESISTANCE: 70 m Ω max.  
 INSULATION RESISTANCE: 100 M Ω min. @ 500V.  
 DIELECTRIC STRENGTH: 500 VAC min.  
 OPERATING TEMPERATURE: -20°C to +85°C for PCM12SMTR.  
 OPERATING TEMPERATURE: -10°C to +85°C for PCM13SMTR.  
 SOLDERABILITY: 255C max. solder temperature.  
 PACKAGING: Tape & reel.

## Materials


CASE: PPA  
 COVER: Stainless steel.  
 SLIDER: Nylon 4/6  
 CONTACTS: Copper alloy silver or gold plated  
 TERMINALS: Copper alloy, silver or gold plated

**NOTE:** All models RoHS compliant and compatible with all options.

**NOTE:** Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.


## How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.




# PCM Series Ultraminiature Surface Mount Slide Switches

## PC MOUNTING



PART NUMBER	SWITCH FUNCTION	
	POS. 1	POS. 2
<b>PCM12SMTR</b>	ON	ON
CONN. TERMINALS	1-2	2-3
SCHMATIC	①	② ③
SPDT		

**PCM12SMTR**  
**SPDT**




Actuator shown in pos. 2

## TAPE & REEL

For part number PCM12SMTR

Quantity per reel 3500




# PCM Series Ultraminiature Surface Mount Slide Switches



PCM13SMTR  
SP3T


PART NUMBER	SWITCH FUNCTION		
	POS. 1	POS. 2	POS. 3
<b>PCM13SMTR</b>	ON	ON	ON
CONN. TERMINALS	1-3	2-3	3-4
SCHMATIC			
SP3T			



## TAPE & REEL

For part number PCM13SMTR

Quantity per reel 3500



Third Angle  
Projection

Dimensions are shown: Inches (mm)  
Specifications and dimensions subject to change



Slide