




## **UD18-9-9-SS**

Ruland UD18-9-9-SS, 9/16" x 9/16" Double Universal Joint, Friction Bearing, Stainless Steel, 1.120" OD, 5.125" Length





## **Description**

Ruland UD18-9-9-SS is a double cardan friction bearing universal joint with 0.5625" x 0.5625" bores, 1.120" OD, and 5.125" length. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD18-9-9-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT18/29-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

**Product Specifications** 

Pins and Blocks: 416 St Steel  Manufacturer Belden Universal Country of Origin USA  Weight (Ibs) 1.030000 Recommended Lubricant LUBRIPLATE No. 1200  Matching Boot Cover UBOOT18/29-NI-KIT UPC 634529288450  Tariff Code 8483.60.4000 UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65 ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	caaci opeciiicaiiciic			
Joint Outer Diameter (OD)  1.120 in  Bore Tolerance +0.0010 in / -0.0000 in  Length (L) 5.125 in Center Yoke Length (LC) 1.625 in  Yoke Length (LY) 1.750 in Hub Depth (LH) 1.220 in  Peak Torque 2025 in-lb Rated Torque 405 in-lb  Max Operating Angle 90° Material Specification Yokes: 303 Stainless St Pins and Blocks: 416 St Steel  Manufacturer Belden Universal Country of Origin USA  Weight (Ibs) 1.030000 Recommended Lubricant LUBRIPLATE No. 1200  Matching Boot Cover UBOOT18/29-NI-KIT UPC 634529288450 Tariff Code 8483.60.4000 UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular ap Prop 65	Bore (B1)	0.5625 in	Small Bore (B2)	0.5625 in
Length (L)  5.125 in  Center Yoke Length (LC)  1.625 in  Yoke Length (LY)  1.750 in  Hub Depth (LH)  1.220 in  Peak Torque  2025 in-lb  Rated Torque  405 in-lb  Max Operating Angle  90°  Material Specification  Yokes: 303 Stainless St Pins and Blocks: 416 St Steel  Manufacturer  Belden Universal  Country of Origin  USA  Weight (Ibs)  1.030000  Recommended Lubricant  LUBRIPLATE No. 1200  Matching Boot Cover  UBOOT18/29-NI-KIT  UPC  634529288450  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65  WARNING This product can expose you to the chemical Nickel (metallic), known to the State	B1 Max Shaft Penetration	1.220 in	<b>B2 Max Shaft Penetration</b>	1.220 in
Yoke Length (LY)  1.750 in  Rated Torque  2025 in-lb  Rated Torque  405 in-lb  Max Operating Angle  90°  Material Specification  Yokes: 303 Stainless St Pins and Blocks: 416 St Steel  Manufacturer  Belden Universal  Country of Origin  USA  Weight (lbs)  1.030000  Recommended Lubricant  LUBRIPLATE No. 1200  Matching Boot Cover  UBOOT18/29-NI-KIT  UPC  634529288450  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65  WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Joint Outer Diameter (OD)	1.120 in	Bore Tolerance	+0.0010 in / -0.0000 in
Peak Torque  2025 in-lb  Rated Torque  405 in-lb  Max Operating Angle  90°  Material Specification  Yokes: 303 Stainless St Pins and Blocks: 416 St Steel  Manufacturer  Belden Universal  Country of Origin  USA  Weight (lbs)  1.030000  Recommended Lubricant  LUBRIPLATE No. 1200  Matching Boot Cover  UBOOT18/29-NI-KIT  UPC  634529288450  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65  WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Length (L)	5.125 in	Center Yoke Length (LC)	1.625 in
Max Operating Angle90°Material SpecificationYokes: 303 Stainless St Pins and Blocks: 416 St SteelManufacturerBelden UniversalCountry of OriginUSAWeight (lbs)1.030000Recommended LubricantLUBRIPLATE No. 1200Matching Boot CoverUBOOT18/29-NI-KITUPC634529288450Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular apProp 65▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Yoke Length (LY)	1.750 in	Hub Depth (LH)	1.220 in
Pins and Blocks: 416 St Steel  Manufacturer Belden Universal Country of Origin USA  Weight (lbs) 1.030000 Recommended Lubricant LUBRIPLATE No. 1200  Matching Boot Cover UBOOT18/29-NI-KIT UPC 634529288450  Tariff Code 8483.60.4000 UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65 ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Peak Torque	2025 in-lb	Rated Torque	405 in-lb
Weight (lbs)  1.030000  Recommended Lubricant  LUBRIPLATE No. 1200  Matching Boot Cover  UBOOT18/29-NI-KIT  UPC  634529288450  Tariff Code  8483.60.4000  UNSPC  25173810  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65  ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Max Operating Angle	90°	Material Specification	Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel
Matching Boot Cover       UBOOT18/29-NI-KIT       UPC       634529288450         Tariff Code       8483.60.4000       UNSPC       25173810         Note 1       Performance ratings are for guidance only. The user must determine suitability for a particular ap         Prop 65       ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Manufacturer	Belden Universal	Country of Origin	USA
Tariff Code       8483.60.4000       UNSPC       25173810         Note 1       Performance ratings are for guidance only. The user must determine suitability for a particular ap         Prop 65       ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Weight (lbs)	1.030000	Recommended Lubricant	LUBRIPLATE No. 1200-2
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular ap  Prop 65 ▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Matching Boot Cover	UBOOT18/29-NI-KIT	UPC	634529288450
Prop 65WARNING This product can expose you to the chemical Nickel (metallic), known to the State	Tariff Code	8483.60.4000	UNSPC	25173810
	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
to cause cancer of more information go to invite correctings.	Prop 65	▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Califo to cause cancer. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .		