



TECHNICAL

LISTED: UL & CSA
 RATED SUPPLY VOLTAGE: 120VAC
 RATED CURRENT: UP TO 30 AMPS
 RESET TYPE: AUTOMATIC OR MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 5mA +/- 1mA
 OVERLOAD CURRENT: 180 AMPS, 0.45PF
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 ENCLOSURE: NEMA 4X/6P

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530174	30052-1A	2 FT 9.4 IN.	1 FT	AUTO
1301530179	30052-6A	7 FT 9.4 IN.	6 FT	AUTO
1301530176	30052-25A	26 FT 9.4 IN.	25 FT	AUTO
1301530175	30052-1M	2 FT 9.4 IN.	1 FT	MANUAL
1301530180	30052-6M	7 FT 9.4 IN.	6 FT	MANUAL
1301530177	30052-25M	26 FT 9.4 IN.	25 FT	MANUAL

FUNCTIONAL SYMBOLS $F_A = 0$ $F_C = 0$ $F_P = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SCALE: INCH NTS		CURRENT REV DESC: UPDATED LENGTH "L" IN THE TABLE.		
	DIMENSION UNITS: INCH		GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 672829 DRWN: PPURSTANDEL 2021/08/06 CHK'D: DNGUYEN62 2021/08/18 APPR: HKNEELAND 2021/08/31		
	ANGULAR TOL: ± °		4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ±		INITIAL REVISION: DRWN: PPURSTANDEL 2021/07/01 APPR: HKNEELAND 2021/07/30		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING: D-SIZE SERIES: 130153		MATERIAL NUMBER: SEE TABLE CUSTOMER: GENERAL MARKET	
DOCUMENT STATUS: P1 RELEASE DATE: 2021/08/31 17:57:20		DOCUMENT NUMBER: 1301530174 DOC TYPE: PSD DOC PART: 000 REVISION: A1		SHEET NUMBER: 1 OF 1			