


FLK 40/EZ-DR/ 200/SLC

Order No.: 2294649



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294649>

Round cable sets, with 40-pos. socket strips in fixed lengths (50 cm steps) to connect to 32-channel I/O cards of the SLC 500, length 2 m

| Commercial data | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 149017 |
| Note | Made-to-order |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 194 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
03/02/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|---|----------------------|
| General | |
| Nominal voltage U_N | < 50 V AC 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Number of positions | 40 |
| Number of positions, control side | 40 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 40 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 2 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| Test voltage | 500 V AC (50 Hz, 1 min.) |
| External diameter | 10 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |
| Standards/regulations | DIN EN 60352-4 |
| | IEC 352-4 |

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;