

Data sheet | Item number: 790-145

Carrier rail; with special perforations; 1000 mm long; tin-plated; silver-colored



www.wago.com/790-145



Data

Technical data

Main product function

Shield termination

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Physical data

Width	1000 mm / 39.37 inches
-------	------------------------

Material Data

Color	silver-colored
Weight	256 g

Commercial data

eCl@ss 10.0	27-40-06-02
eCl@ss 9.0	27-40-06-02
ETIM 8.0	EC001285
ETIM 7.0	EC001285
PU (SPU)	1 pcs
Packaging type	box
Country of origin	IT
GTIN	4045454701109
Customs tariff number	72169180000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Optional accessories

Shield termination

Shield termination

Item no.: 790-144

Stand off; for carrier rail; suitable for M5 size screw; with special perforations
--

www.wago.com/790-144
--

Downloads

Documentation

Bid Text

790-145 X81 - Datei	2019 年2月19 日	xml 2.6 kB	Download
790-145 doc - Datei	2017 年8月31 日	doc 23.6 kB	Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



CAD/CAE-Data

CAE data

WSCAD Universe 790-145	URL	Download
ZUKEN Portal 790-145	URL	Download
EPLAN Data Portal 790-145	URL	Download

CAD data

2D/3D Models 790-145	URL	Download
----------------------	---------------------	--------------------------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 790-145 Carrier rail; with special perforations; 1000 mm long; tin-plated; silver-colored	URL	Download
---	---------------------	--------------------------

Installation Notes



Securing a spacer sleeve to a specialty slotted DIN-rail.


Subject to changes. Please also observe the further product documentation!



Securing an additional shield clamping saddle.



Tightening/removing a shield clamping saddle.



After connection, tighten the knurled screw to complete the installation.

Recommended tightening torque: 0.5 Nm



To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.

Subject to changes. Please also observe the further product documentation!