

1	2	3	4
Product P/N	Connector P/N	Position NO	Cable description
1IC03622051701	40002453-01-001	2	900-00201-00112 NOUL 2C*26AWG TPU OD3.1
1IC03622051702	40003453-01-001	3	900-00301-00093 NOUL 3C*26AWG TPU OD3.1
1IC03622051703	40004453-01-001	4	900-00401-00146 NOUL 4C*0.14mm ² TPU OD3.7
1IC03622051704	40005453-01-001	5	900-00501-00056 NOUL 5C*0.14mm ² TPU OD3.7
1IC03622051705	40006453-01-001	6	900-00601-00062 NOUL 6C*26AWG TPU OD4.1

5	6	7	8
REV.	ECN NO.	DATE	SIGN
C1	NA	2022/08/15	XU
			DESCRIPTION
			First Version

CABLE 1:


6P	Pin	Color
6	6	VIOLET
5	5	GREEN
4	4	BLACK
3	3	BLUE
2	2	YELLOW
1	1	RED

5P	Pin	Color
5	5	BLACK
4	4	WHITE
3	3	BROWN
2	2	ORANGE
1	1	RED

4P	Pin	Color
4	4	WHITE
3	3	BROWN
2	2	ORANGE
1	1	RED

3P	Pin	Color
3	3	BLUE
2	2	YELLOW
1	1	RED

2P	Pin	Color
2	2	YELLOW
1	1	RED



Connector P/N See CABLE 1

- Specification:
1. Operating temperature: -25°C ~ +80°C.
 2. Current Rating: 2A
 3. Voltage Rating: 48VAC, 60VDC.
 4. Insulation resistance: 10MΩ at 300VDC.
 5. Mating cycles: 200 cycles.
 6. Waterproof: IP66 (Mated).
 7. RoHS compliant.

No.	Material No.	Q'ty	Unit	Material Description
3	900-00***-00***	A/R	M	Cable 2C~6C Range Maxφ4.5 0.14mm ² ~0.2mm ² Other Requirements Can Be Customized
2	504-00011-00	A/R	M	Heat Shrink Tube OD1.5
1	4000*453-01-001	1	PC	Micro Series * Pin Female Connector

Material List

ITEM NO.	11C036220517**	DRAWN BY	XU	DATE	2022/08/15
DWG NO.	11C036220517**	CHECKED BY	Kevin	DATE	2022/08/15
CUSTOMER NO.		REV.		APPROVED BY	

UNIT:mm	TITLE
未注线性和角度尺寸公差 UNSPECIFIED TOLERANCE	Micro series molding socket Female connector
SCALE N/A	SHEET 1 of 1
REV. C1	SIZE A4 * Inspection Item

CHOGORI
Chogori Technology Co., Ltd

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.