



Scan the QR code and visit the product page



Code	TK.LB.W0610S.AEC	Safety level	Warning
Dimensions (H x L)	34 mm x 80 mm (2,7" x 3,1")	Version	Small
Material	PVC base with adhesive liner and protective layer	Temperatures ⁽¹⁾	-40°C/+95°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages ⁽²⁾	English		
Message ⁽³⁾	EN: Electric Shock Hazard. Main disconnect switch does not remove UPS output power. Read and understand operator's manual before turning off UPS and servicing. IT: Pericolo di shock elettrico. Il sezionatore principale non rimuove la tensione in uscita dall'UPS. Leggere e comprendere il manuale dell'operatore prima di spegnere l'UPS e per la manutenzione.		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.