



REV	DATE	DESCRIPTION	BY	CHK'D
00	12/28/87	REVISED PER ECU-88-00737	H	BMI

1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.

MATERIAL:

COVER & CABLE - THERMOPLASTIC, BLACK.
 TERMINALS - PHOS BRONZE PLATED WITH EITHER .000030 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000030 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.

2. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
3. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
4. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
5. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
6. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
7. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-8078 & APPLICATION SPEC 114-6030.

THIS DRAWING IS A CONTROLLED DOCUMENT		REV. 15/04/97	
DIMENSIONS IN INCHES		REV. 15/04/97	
DIMENSIONS IN MILLIMETERS		REV. 15/04/97	
DRAWN BY: M. MILLIENES		DESIGNED BY: M. MILLIENES	
CHECKED BY: J. G. MCNEIL		APPROVED BY: J. G. MCNEIL	
DATE: 12/28/87		DATE: 12/28/87	
APPLICATION SPEC: ---		PART NO: A2100779	
CUSTOMER DRAWING: ---		PART NO: 553598	
SCALE: 2:1		SHEET: 1 OF 1	

AS SHOWN 553598-1
 DESCRIPTION PART NUMBER