


Fuse terminals

SAKS 3 SAKS 3/35



| | |
|--|-------------------------------|
| | |
| Width/length/height (mm) with TS 32 | 13/54/61 |
| Width/length/height (mm) with TS 35 x 7.5 | 13/54/55 |
| Insulation stripping length/clamping screw/screwdriver blade | 12 mm/M 4/5.5 x 1 |
| Rated data/feed through-terminal base | |
| Rated voltage/current/cross-section | 500 V/10 A/10 mm ² |
| Rated impulse voltage/pollution severity | 6 kV/3 |
| Further technical data | |
| Tightening torque range | Nm 1.2...2.4 |
| Torque setting with electric screwdriver type DMS 2 | 4 |
| Clampable conductor | |
| Solid H07V-U | mm ² 0.5...16 |
| Stranded H07V-R | mm ² 1.5...10 |
| Flexible H07V-K | mm ² 0.5...10 |
| Flexible H07V-K and ferrule according to DIN 46 228/1 | mm ² 0.5...10 |
| Plug gauge according to 60 947-7-1 | Size B 6 |
| Continuous current rating of cross-connection 2...5-pole | A (QL 2...5) 47 |
| Continuous current rating of cross-connection 6...10-pole | A (QL 6...10) 36 |

SAKS 4 SAKS 4/35



| | |
|--|---------------------------------|
| | |
| Width/length/height (mm) | 24/75/73 |
| Width/length/height (mm) | 24/75/66 |
| Insulation stripping length/clamping screw/screwdriver blade | 14 mm/M 4/5.5 x 1 |
| Rated data/feed through-terminal base | |
| Rated voltage/current/cross-section | 400 V**/16 A/10 mm ² |
| Rated impulse voltage/pollution severity | 6 kV/3 |
| Further technical data | |
| Tightening torque range | Nm 1.2...2.4 |
| Torque setting with electric screwdriver type DMS 2 | 4 |
| Clampable conductor | |
| Solid H07V-U | mm ² 0.5...16 |
| Stranded H07V-R | mm ² 1.5...10 |
| Flexible H07V-K | mm ² 0.5...10 |
| Flexible H07V-K and ferrule according to DIN 46 228/1 | mm ² 0.5...10 |
| Plug gauge according to 60 947-7-1 | Size B 6 |
| Continuous current rating of cross-connection 2...5-pole | A (QL 2...5) 47 |
| Continuous current rating of cross-connection 6...10-pole | A (QL 6...10) 36 |

SAKS 5 SAKS 5/35



| | |
|--|----------------------------------|
| | |
| Width/length/height (mm) | 28/80/80.5 |
| Width/length/height (mm) | 28/80/66 |
| Insulation stripping length/clamping screw/screwdriver blade | 13 mm/M 4/5.5 x 1 |
| Rated data/feed through-terminal base | |
| Rated voltage/current/cross-section | 400 V/63 A***/16 mm ² |
| Rated impulse voltage/pollution severity | 6 kV/3 |
| Further technical data | |
| Tightening torque range | Nm 1.2...2.4 |
| Torque setting with electric screwdriver type DMS 2 | 4 |
| Clampable conductor | |
| Solid H07V-U | mm ² 1.5...16 |
| Stranded H07V-R | mm ² 1.5...16 |
| Flexible H07V-K | mm ² 1.5...16 |
| Flexible H07V-K and ferrule according to DIN 46 228/1 | mm ² 1.5...16 |
| Plug gauge according to 60 947-7-1 | Size B 7 |
| Continuous current rating of cross-connection 2...5-pole | A (QL 2...5) 47 |
| Continuous current rating of cross-connection 6...10-pole | A (QL 6...10) 36 |

SAKS 2 SAKS 2/35



| | |
|--|---------------------------------------|
| | |
| Width/length/height (mm) | 28/80/81.5 |
| Width/length/height (mm) | 28/80/75 |
| Insulation stripping length/clamping screw/screwdriver blade | 12 mm/M 4/5.5 x 1 |
| Rated data/feed through-terminal base | |
| Rated voltage/current/cross-section | 500 V/10 (25) A***/10 mm ² |
| Rated impulse voltage/pollution severity | 6 kV/3 |
| Further technical data | |
| Tightening torque range | Nm 1.2...2.4 |
| Torque setting with electric screwdriver type DMS 2 | 4 |
| Clampable conductor | |
| Solid H07V-U | mm ² 0.5...16 |
| Stranded H07V-R | mm ² 0.5...10 |
| Flexible H07V-K | mm ² 0.5...10 |
| Flexible H07V-K and ferrule according to DIN 46 228/1 | mm ² 0.5...10 |
| Plug gauge according to 60 947-7-1 | Size B 6 |
| Continuous current rating of cross-connection 2...5-pole | A (QL 2...5) 47 |
| Continuous current rating of cross-connection 6...10-pole | A (QL 6...10) 36 |

Dimensions/approvals

| | | |
|--|------------------|--|
| Width/length/height (mm) | with TS 32 | |
| Width/length/height (mm) | with TS 35 x 7.5 | |
| Insulation stripping length/clamping screw/screwdriver blade | | |

Rated data/feed through-terminal base

| | |
|--|-------------------------------|
| Rated voltage/current/cross-section | 500 V/10 A/10 mm ² |
| Rated impulse voltage/pollution severity | 6 kV/3 |

Further technical data

| | |
|---|--------------|
| Tightening torque range | Nm 1.2...2.4 |
| Torque setting with electric screwdriver type DMS 2 | 4 |

Clampable conductor

| | |
|---|--------------------------|
| Solid H07V-U | mm ² 0.5...16 |
| Stranded H07V-R | mm ² 1.5...10 |
| Flexible H07V-K | mm ² 0.5...10 |
| Flexible H07V-K and ferrule according to DIN 46 228/1 | mm ² 0.5...10 |
| Plug gauge according to 60 947-7-1 | Size B 6 |
| Continuous current rating of cross-connection 2...5-pole | A (QL 2...5) 47 |
| Continuous current rating of cross-connection 6...10-pole | A (QL 6...10) 36 |

Rated data according to UL/CSA

| | | |
|--------------------------------|-----|------------------------|
| Voltage/current/conductor size | UL | 300 V/10 A/22...10 AWG |
| Voltage/current/conductor size | CSA | 600 V/10 A/22...10 AWG |

Ordering data

| | | | | |
|---------|------------------------------------|------------------------------------|--|------|
| Version | | Qty. | | Qty. |
| KrG | 0248920000 ³⁾ 20 | 0667520000 ³⁾ 20 | | |
| KrG | 0297520000 ⁴⁾ 20 | 0328920000 ⁴⁾ 20 | | |

Neozed D 01

| | | |
|----------|-------------------|------|
| Type | Cat. No. | Qty. |
| AP (2.5) | 0191320000 | |
| HP for | | |
| TW (2.0) | 0607000000 | |

Neozed D 02

| | | |
|-------------|---------------------------------|------|
| Type | Cat. No. | Qty. |
| TW HP (2.0) | 0607000000 ²⁾ | |


Diazed E 16

| | | |
|-------------|---------------------------------|------|
| Type | Cat. No. | Qty. |
| TW HP (2.0) | 0607000000 ²⁾ | |

End plate/partition (thickness mm)

| | | | |
|----|----------|-------------------|------|
| PA | Type | Cat. No. | Qty. |
| HP | AP (2.5) | 0191320000 | |
| | HP for | | |
| | TW (2.0) | 0607000000 | |

Cross-connection



Fixing screws for cross-connections

Fuse inserts

| | | |
|---------------|----------------------|---------------------------|
| 1 1/4" x 1/4" | Nominal current (A): | Fuse insert |
| | 0.5 fast | E 0.5 A 0533800000 |
| | 1.0 fast | E 1 A 0525500000 |
| | 2.0 fast | E 2 A 0294500000 |
| | 3.0 fast | E 3 A 0295700000 |
| | 5.0 fast | E 5 A 0294600000 |
| | 7.0 fast | E 7 A 0295800000 |
| | 10.0 fast | E 10 A 0293900000 |

G fuse inserts 5 x 30 mm

(500 V~/0.032...6.3 A).

Available from Wickmann-Werke GmbH, Annastr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts

| | |
|---------------------|----------------------|
| Rated voltage 400 V | |
| E 14/2 | 0137400000 10 |
| E 14/4 | 0137500000 10 |
| E 14/6 | 0328300000 10 |
| E 14/10 | 0328400000 10 |
| E 14/16 | 0328500000 10 |

| | |
|---------------------|----------------------|
| Rated voltage 400 V | |
| E 18/20 | 0361300000 10 |
| E 18/25 | 0361400000 10 |
| E 18/35 | 0361500000 10 |
| E 18/50 | 0361600000 10 |
| E 18/63 | 0361700000 10 |

| | |
|---------------------|----------------------|
| Rated voltage 500 V | |
| E 10 A | 0208500000 25 |
| E 16 A | 0208600000 25 |
| E 20 A | 0208700000 25 |
| E 25 A | 0208800000 25 |

Screw cap (spare)

| | | |
|-------|------------------|----------------------|
| red | SK (5 x 30) | 0282000000 20 |
| black | SK (1/4"x1 1/4") | 0428900000 20 |

SK **0339410000** 20

SK **0359310000** 20

SK **0284110000** 20

Marking tags

| | | | |
|--|-----|-------|----------|
| | DEK | Print | Standard |
|--|-----|-------|----------|

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ only for TS 32

²⁾ Also for 440 V- with neozed marina fuse
³⁾ Current for overload up to 10 A, for short circuit up to 25 A

³⁾ For fuse inserts 1 1/4 x 1/4" DEF 63
⁴⁾ For fuse inserts 5 x 30