

## Housing - HC-D 50-TMQ-76/O1M32G - 1604919


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HEAVYCON sleeve housing D50, with double locking latch, height 76 mm, with support 1x M32, straight conductor exit



### Key commercial data

|                                      |  |
|--------------------------------------|--|
| Packing unit                         | 1 PCE  |
| GTIN                                 | <br>4 017918 882983 |
| Weight per Piece (excluding packing) | 400.0 GRM  |
| Custom tariff number                 | 85389099   |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|        |       |
|--------|-------|
| Height | 76 mm |
| Width  | 56 mm |
| Length | 82 mm |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|                    |                                     |
|--------------------|-------------------------------------|
| Note               | For contact inserts HC-D25, A16/A32 |
| Design             | D50                                 |
| Housing type       | Sleeve housings                     |
| Locking type       | With double locking latch           |
| No. of cable exits | 1                                   |

# Housing - HC-D 50-TMQ-76/O1M32G - 1604919

## Technical data

### General

|                              |                     |
|------------------------------|---------------------|
| Cable exit                   | Straight            |
| Screw connection             | None                |
| Type of the screw connection | 1x M32              |
| Housing material             | Aluminum die-cast   |
| Housing surface material     | Powder-coated, gray |
| Material lock                | Steel, galvanized   |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Approvals

### Approvals

---

Approvals

GOST

---

## Housing - HC-D 50-TMQ-76/O1M32G - 1604919

### Approvals


Ex Approvals

---

Approvals submitted

---

### Approval details



### Accessories

#### Accessories

#### Full screw connection

Cable gland - HC-K-KV-M32(15-21) - 1690642



Plastic screw connection up to 5 bar, thread length: 10 mm, cable diameter: 15 - 21 mm, WAF 36, screw connection: M32

---

Cable gland - HC-M-KV-M32(14-21) - 1690587



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M32

---

Cable gland - HC-M-KV-M32(19-27) - 1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

---

### Drawings

# Housing - HC-D 50-TMQ-76/O1M32G - 1604919

Dimensioned drawing

