0.25 METER LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot

Connector B 2FA1-NZSP-C01Y1 FAKRA Plug Straight Zinc Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| Connector A | | Cable | | | Connector B | |
|-------------------|-----------------------------------|--------------|-------------------|-------------------|----------------------------|--|
| Part #: | 132245 | Part #: | RG-174 | Part #: | 2FA1-NZSP-C01Y1 | |
| Description: | SMA R/A BHD JK RG174 RG316 LMR100 | Description: | RG-174 - PE 0.1 | Description: | FAKRA-Z PL RG174 RG316 500 | |
| Description. | 50O | Dielectric: | PE | Type: | FAKRA | |
| Type: | SMA | Shielding: | Braid | Gender: | Plug | |
| Gender: | Jack | Diameter: | 0.1 | Body Type: | Straight | |
| Body Type: | Right Angle | Impedance: | 50 Ohm | Contact Type: | Crimp | |
| Contact Type: | Solder | Sheathing: | None | Polarity: | Standard | |
| Polarity: | Standard | Testing: | Continuity Hi-Pot | Impedance: | 50 Ohm | |
| Impedance: | 50 Ohm | Length: | 0.25 Meter | Mounting: | Cable | |
| Mounting: | Bulkhead - Rear Mount | | | Body Material: | Zinc | |
| Body Material: | Brass | | | Body Finish: | Nickel | |
| Body Finish: | Gold | | | IP Rating: | None | |
| IP Rating: | None | | | Contact Material: | Brass | |
| Contact Material: | Beryllium Copper | | | Contact Finish: | Gold | |
| Contact Finish: | Gold | | | Max. Freq.: | 3 GHz | |
| Max. Freq.: | 12.4 GHz | | | Booting: | FAKRA-Z Plug Straight | |
| Booting: | SMA Jack Right Angle | | | Clocking: | 0° | |



INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

THIS DRAWING MAY CONTAIN PATENTED OR

SMA-RA-JK/FKRAZ-ST-PL G174 0.25M PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES

UNLESS SPECIFIED

Q-2P05A0003.25M

CONTROLLED DOCUMENT - DO NOT COPY