


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00045	Connector, dc jack, 3.5x1.1xL16.5 mm, molding style	1	
2	30-00404	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A	1	
3	24-00005	Overmold, PVC	1	black



Wiring Diagram	
50-00045	wire color
center	black with stripe
sleeve	black

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1>
A	10/3/2017	Initial release	AG <small>Digitally signed by AG Date: 2017.10.05 14:08:07 -0700'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 3.5x1.1 mm 50-00045 dc jack to 10 mm tinned, 24 AWG, UL2468, 30-00404 wire	Size: A Part number: 10-02514
					Scale: 1:1 Sheet 1 of 1

5

4

3

2

1