


Outline

- LEAD WIRE SIDE
- HSG: 51021-0600
- PIN : 50079-8000




Motor frame size of 28mm is also available.



UNIT: mm
(inch)

Hybrid

- LEAD WIRE SIDE
- HSG: 51021-0600
- PIN : 50079-8000



UNIT: mm
(inch)

	"L"
10PM-K2**	23.5(0.92)
10PM-K0**	27.5(1.08)
10PM-K7**	33(1.3)
10PM-K1**	40.5(1.59)
10PM-K4**	51.5(2.03)

PIN NO. vs. PHASE


PHASE	A	B	\bar{A}	\bar{B}
PIN NO.	4	1	6	3

Specifications


Model	Step Angle	Drive Sequence	Rated Current	Resistance	Holding Torque	Inductance	Rotor Inertia	Detent Torque	Mass
	deg		A	Ohms	mNm	mH	g cm ²	mNm	g
10PM-K013B	1.8	BI-POLAR	0.21	47.0	49	30.0	3	2.5	70
10PM-K105B	1.8	BI-POLAR	1.5	1.2	90	1.0	8	4.0	110
10PM-K106B	1.8	BI-POLAR	1.0	2.8	90	2.5	8	4.0	110
10PM-K202B	1.8	BI-POLAR	0.7	3.8	33	2.0	2	2.0	55
10PM-K405B	1.8	BI-POLAR	1.5	1.6	120	1.6	12	5.0	150
10PM-K406B	1.8	BI-POLAR	1.0	3.8	120	3.6	12	5.0	150
10PM-K701B	1.8	BI-POLAR	0.63	5.8	62	5.4	5	3.0	90

Torque/Speed Characteristics


Model No: 10PM-K013B/K202B/K701B
Driver: Chopper Dual
Supply Voltage: 24.0 (Volt)



Model No: 10PM-K105B/K106B
Driver: Chopper Dual
Supply Voltage: 24.0 (Volt)



Model No: 10PM-K405B/K406B
Driver: Chopper Dual
Supply Voltage: 24.0 (Volt)



— : PULL OUT
- - - : PULL IN