

Ŧ	<mark>م</mark>	п –	m	O







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

BASIC SERIES:

SHELL SIZE : 13

PLATING : M = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ω

-Standard : Based on MIL-DTL-38999 Series III

	-Shell Material	: Composite
	-Shell Plating	: Nickel
	-Insulator	: Thermoplastic
	-Contacts	: Copper Alloy
	-Seals & Grommet	: Silicon Elastomer
N	-Contact Plating	: Gold over copper Alloy 0.8µm minimum
	-Durability	: 500 Mating cycles
	-Delivered with Souria	u contacts and Accessories
	-Temperature Range	65°C to +200°C
	-Salt Spray	: 2000 hours
	-Mass	: 14.1 g ± 10%

8D 0

G

13

Μ

08

А

F

D

Dim	Nominal
Р	3.25±0.2
PP	4.93±0.2
R1	23.01
R2	20.62
S	28.6±0.3
V'	19.5+1.4/-0
W'	2.1/3.65
Z'	32 Max
VV THREAD	M18x1-6g


ORIENTATION : D

D

CONTACT TYPE : PIN(500 Matings)

Е

CONTACT LAYOUT : 13-08





С

	Ξ		A		
					4
SS EXA	AMPLE				3
whice er of t idatic untry R	non-conformit ch does not co the Parties or b on, technical no Jurisd	mply with by a third part			2
		CUSTOME	R DRAWING	MOD N°	
ite Receptacle 8D series					
ar			PROJECT		1
I.CC	.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	U DRG N° SHEET				
M0	8AD-C	I		1/2]
	В		А		

		۵	ات	m		0
		Contact Layout				Panel Cutout
4		$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & $			Å	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
	Com posi II A E CC C C C C C C C C C C C C C C C N S S C N S S S S	Jon X-axis (mm) Y-axis (mm) 4 +.065 (1.65) +.157 (3.99) 8 +.170 (4.32) +.000 (0.00) > +.120 (3.05) 120 (3.05) > 170 (4.32) +.000 (0.00) E 120 (3.05) 120 (3.05) 170 (4.32) +.000 (0.00) S 065 (1.65) +.157 (3.99)			¥ 	
ى ع		mber of Size Service Contact Supersedes ntacts contacts rating location 8 8 20 I All MS20051-8				Dim ØA ØAA R1 ØT
						SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendati
23						Country FR PN: 8D013N
					A 15-10-20 ISS DATE Designed By:	16 First Release
_					TITLE SCALE NA	General linear Tolerances:
					SOURIA	
		1	1		FORMAT A3	SOURIAU 8D013M0
	Н	G	F	E	D	C

