

MML4400 Series Datasheet
RoHS-Compliant Fast Surface Mount MRI
Protection Diodes



**Microsemi Corporate Headquarters**

One Enterprise, Aliso Viejo,
CA 92656 USA

Within the USA: +1 (800) 713-4113

Outside the USA: +1 (949) 380-6100

Fax: +1 (949) 215-4996

Email: sales.support@microsemi.com

www.microsemi.com

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

About Microsemi

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California, and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

1 Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

1.1 Revision 1.0

Revision 1.0 was the first publication of this document.

Contents

1	Revision History.....	3
1.1	Revision 1.0.....	3
2	Product Overview	7
2.1	Applications	7
2.1.1	Benefits.....	7
2.2	Key Features.....	8
3	Electrical Specifications.....	9
3.1	Absolute Maximum Ratings	9
3.2	Device Electrical Parameters.....	9
3.3	Typical Rs Performance	10
4	Package Outline.....	11
4.1	GM2 Package Outline	11
4.2	GM3 Package Outline	13
5	Tape-and-Reel Format.....	15
5.1	GM2 Tape-and-Reel Format.....	15
5.2	GM3 Tape-and-Reel Format.....	16
6	Ordering Information	17

List of Figures

Figure 1 GM2 Package Option	7
Figure 2 GM3 Package Option	7
Figure 3 Typical Rs Performance.....	10
Figure 4 GM2 Package Outline.....	11
Figure 5 GM3 Package Outline.....	13
Figure 6 GM2 Tape-and-Reel Format	15
Figure 7 GM3 Tape-and-Reel Format	16



List of Tables

Table 1	Absolute Maximum Ratings	9
Table 2	Device Electrical Parameters	9
Table 3	GM2 Package Dimensions	12
Table 4	GM3 Package Dimensions	14
Table 5	Ordering Information	17

2 Product Overview

There are two principal applications for which the MML4400 series are intended.

The first is MRI receiver protection from high-RF energy fields, including long RF pulses and RF spike pulses present in most MRI machines. The MML4400 series acts as a passive protector (limiter) for the MRI receiver's low-noise amplifier (LNA). The diode assembly exhibits extremely low insertion loss, both in the on state (high power present) and the off state (receiver power present), so that the receiver's noise figure is not increased by the protector circuit.

The second principal application is passive switching of surface-coil detuning and blocking circuits. In this case, the flow of the loop current during transmitter pulses turns on the diodes, without the use of a switch driver.

The following illustrations show the primary functional blocks of the MML4400 series devices.

Figure 1 GM2 Package Option





Figure 2 GM3 Package Option



2.1 Applications

The MML4400 series can be combined with a PIN diode (UM7201SM), and the combination can be used to implement a semi-active detune or block circuit design. The MML4400 series devices turn on the PIN diode (used for higher-power switching) during the sinc(x) sidelobes, before the main pulse of the transmitter waveform ($\text{sinc}(x) = [\sin(x)]/x$) occurs.

This surface mount limiter meets RoHS requirements according to EU directives 2011/65/EC and 2002/95 EC.

2.1.1 Benefits

The MML4400 series devices provide the following application benefits:

- MRI passive receiver protection

- MRI passive blocking circuits
- MRI passive detuning circuits
- MRI passive disable circuits

2.2 Key Features

The following are key features of the MML4400 series devices:

- Designed for MRI applications
- Anti-parallel (unconnected pairs) option available with GM3 package
- Low capacitance at 0 V bias: 1.5 pF maximum
- Low conductance at 0 V bias: 40 μ s maximum at F = 64 MHz
- Low magnetic construction surface mount package
- RoHS compliant and 260 °C reflow compatible
- Passivated chip
- Compatible with automatic insertion equipment

3 Electrical Specifications

3.1 Absolute Maximum Ratings

The following table shows the absolute maximum ratings at 25 °C unless otherwise specified.

Table 1 Absolute Maximum Ratings

Rating	Symbol	Value	Unit
Maximum leakage current (at 80% of minimum-rated V_b)	I_R	0.5	μA
Operating temperature	T_{OP}	-55 to 150	$^{\circ}\text{C}$
Storage temperature	T_{STG}	-65 to 150	$^{\circ}\text{C}$
ESD sensitivity (HBM)		Class 1A	
Moisture sensitivity level		MSL 1	

3.2 Device Electrical Parameters

The following table shows the device electrical parameters at 25 °C. Specifications for the GM3 configurations are based on a single diode in anti-parallel topology.


Table 2 Device Electrical Parameters

Model Number	V_b $I_R = 10 \mu\text{A}$ (Min)	C_{T0} at 0 V (Max)	R_S at 100 mA $f = 100 \text{ MHz}$ (Max)	T_L (Typ)	Conductance (G) $V_r = 0 \text{ V}$ $F = 64 \text{ MHz}$ (Max)	θ_P Thermal Resistance (Max)
MML4401-GM2	75 V	1.5 pF	2.5 Ω	10 ns	40 μs	20 $^{\circ}\text{C/W}$
MML4401-GM3	75 V	1.5 pF	2.5 Ω	10 ns	40 μs	20 $^{\circ}\text{C/W}$
MML4402-GM2	75 V	2.0 pF	1.5 Ω	20 ns	40 μs	20 $^{\circ}\text{C/W}$
MML4402-GM3	75 V	2.0 pF	1.5 Ω	20 ns	40 μs	20 $^{\circ}\text{C/W}$
MML4403-GM2	75 V	1.5 pF	1.0 Ω	30 ns	40 μs	30 $^{\circ}\text{C/W}$
MML4403-GM3	75 V	1.5 pF	1.0 Ω	30 ns	40 μs	30 $^{\circ}\text{C/W}$

3.3 Typical Rs Performance

The following graph shows the typical Rs performance of the MML4400 series devices, where $f = 100 \text{ MHz}$.

Figure 3 Typical Rs Performance




4 Package Outline

4.1 GM2 Package Outline

The following illustration shows the GM2 package outline of the MML4400 series devices.

Figure 4 GM2 Package Outline



The following table shows the GM2 package dimensions of the MML4400 series devices.


Table 3 GM2 Package Dimensions

DIM	Inches			Millimeters		
	Min	Typ	Max	Min	Typ	Max
A	0.045	0.050	0.055	1.143	1.270	1.397
B	0.075	0.080	0.085	1.905	2.032	2.159
C	0.030	0.035	0.040	0.762	0.889	1.016
D			0.003			0.076
E		0.046			1.168	
F		0.044			1.118	
G		0.011			0.279	
H		0.006			0.152	

4.2 GM3 Package Outline

The following illustration shows the GM3 package outline of the MML4400 series devices.

Figure 5 GM3 Package Outline



The following table shows the GM3 package dimensions of the MML4400 series devices.

Table 4 GM3 Package Dimensions


DIM	Inches			Millimeters		
	Min	Typ	Max	Min	Typ	Max
A	0.094	0.099	0.104	2.388	2.515	2.642
B	0.093	0.098	0.103	2.362	2.489	2.616
C	0.030	0.035	0.040	0.762	0.889	1.016
D			0.003			0.076
E		0.085			2.159	
F		0.084			2.134	
G		0.050			1.270	
H		0.0120			0.254	
J		0.025			0.635	
K		0.035			0.889	
L		0.014			0.356	

5 Tape-and-Reel Format

5.1 GM2 Tape-and-Reel Format

The following illustration shows the GM2 tape-and-reel format of the MML4400 series devices in inches and millimeters.


Figure 6 GM2 Tape-and-Reel Format



5.2 GM3 Tape-and-Reel Format

The following illustration shows the GM3 tape-and-reel format of the MML4400 series devices in inches and millimeters.

Figure 7 GM3 Tape-and-Reel Format



6 Ordering Information

The following table shows the ordering information for the MML4400 series devices.

Table 5 Ordering Information

Part Number	Package
MML4401-GM2	GM2
MML4401-GM3	GM3
MML4402-GM2	GM2
MML4402-GM3	GM3
MML4403-GM2	GM2
MML4403-GM3	GM3