1 METER LENGTH





Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B SMP-FR-C08-1 SMP Plug Right Angle Beryllium Copper Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132114RP	Part #:	RG-174	Part #:	SMP-FR-C08-1	
Description:	SMA PLUG RP RG316 500	Description:	RG-174 - PE 0.1	Description:	SMP R/A PLUG RG316 RG174 500	
Type:	SMA	Dielectric:	PE	Type:	SMP	
Gender:	Plug	Shielding:	Braid	Gender:	Plug	
Body Type:	Straight	Diameter:	0.1	Body Type:	Right Angle	
Contact Type:	Crimp	Impedance:	50 Ohm	Contact Type:	Solder	
Polarity:	Reverse	Sheathing:	None	Polarity:	Standard	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:	Cable	Length:	1 Meter	Mounting:	Cable	
Body Material:	Brass			Body Material:	Beryllium Copper	
Body Finish:	Gold			Body Finish:	Gold	
IP Rating:	None			IP Rating:	None	
Contact Material:	Beryllium Copper			Contact Material:	Beryllium Copper	
Contact Finish:	Gold			Contact Finish:	Gold	
Max. Freq.:	12.4 GHz			Max. Freq.:	26.5 GHz	
Booting:	SMA Plug Straight RP			Booting:	SMP Plug Right Angle	
-				Clocking:	0°	



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-PL-RP/SMP-RA-PL G174 1M

Part No

Q-680420003001M

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES

CONTROLLED DOCUMENT - DO NOT COPY