

		Date SYM
		MAS
		REVISION RECORD AUTH DR. CK.
		AUTH
		JR.
		<u> </u>

	-	6.30 [0.25]	-	
( '7		9		
				12.90 [0.51]
	<u> </u>	_)		

-	τ	J
	П	٦
•	$\mathcal{C}$	
•	₹	1
	7	)
	Ì	>
	Ξ	
-	$\overline{C}$	2
J	6	<u> </u>
-		•

SPECIFICATIONS:
Plastic Material: Polypropylene
Flammability rating: UL94 HB,
Temperature Range: -10°C to +100°C
Springs: Nickel Plated Spring Steel
Rivets: Brass, Nickel Plated

9V Snaps: Brass, Nickel Plated Contact resistance: Under  $50m\Omega$  for +/- contacts per EIA-540J000 ROHS 2 COMPLIANT

Angular ± 3°	Fractional ± .8 (.030)	±.5 (.020)	Decimal		Tolerance (Inches)
Date 05/01/15	Title 6,			200	MPD Memo
Drawing Number BH26AASF-AS	6 'AA' BATTERY HOLDER WITH SNAP FASTENERS		Scale	200 Broad Hollow Road, Farmingdale, New York 11735	MPD Memory Protection Devices, Inc
-AS	ITH SNAP FASTENERS	Approved By T.B.	Scale Drawn By B.S.	dale, New York 11735	Devices, Inc