SIEMENS

Data sheet

3SU1050-1CD20-0AA0-Z Y10



Mushroom pushbutton, 22 mm, round, metal, shiny, red, 60 mm, momentary contact type, with laser labeling, upper case and lower case, always upper case at beginning of line

product brand name	SIRIUS ACT		
product designation	Mushroom pushbuttons		
design of the product	Actuating/signaling element		
product type designation	3SU1		
product line	Metal, shiny, 22 mm		
Enclosure	Enclosure		
number of command points	1		
Actuator			
principle of operation of the actuating element	momentary contact type		
product extension optional light source	No		
color of the actuating element	red		
material of the actuating element	plastic		
shape of the actuating element	round		
outer diameter of the actuating element	60 mm		
marking of the actuating element	Customized labeling, text in lower case / capital letters, all lines start with capital letter		
number of switching positions	2		
Front ring			
product component front ring	Yes		
design of the front ring	Standard		
material of the front ring	Metal, high gloss		
color of the front ring	silver		
General technical data			
product function			
 EMERGENCY OFF function 	No		
 EMERGENCY STOP function 	No		
protection class IP	IP66, IP67, IP69(IP69K)		
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13		
shock resistance			
 according to IEC 60068-2-27 	sinusoidal half-wave 15g / 11 ms		
vibration resistance			
 according to IEC 60068-2-6 	10 500 Hz: 5g		
operating frequency maximum	3 600 1/h		
mechanical service life (switching cycles) typical	10 000 000		
reference code according to IEC 81346-2	S		
Substance Prohibitance (Date)	10/01/2014		
Ambient conditions			
ambient temperature			
• during operation	-25 +70 °C		

• during storage-40 +80 °Cenvironmental category during operation according to IEC 607213M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)Installation/ mounting/ dimensions60 mmwidth60 mmshape of the installation opening mounting diameterroundpositive tolerance of installation diameter0.4 mmmounting height27.5 mminstallation width60 mmcommon time to the positive tolerance of installation diameter24.4 mmCertificates/ approvals24.4 mm		
60721 Installation/ mounting/ dimensions height 60 mm width 60 mm shape of the installation opening round mounting diameter 22.3 mm positive tolerance of installation diameter 0.4 mm mounting height 27.5 mm installation width 60 mm installation depth 24.4 mm	during storage	-40 +80 °C
height60 mmwidth60 mmshape of the installation openingroundmounting diameter22.3 mmpositive tolerance of installation diameter0.4 mmmounting height27.5 mminstallation width60 mminstallation depth24.4 mm		3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
width60 mmshape of the installation openingroundmounting diameter22.3 mmpositive tolerance of installation diameter0.4 mmmounting height27.5 mminstallation width60 mminstallation depth24.4 mm	Installation/ mounting/ dimensions	
shape of the installation openingroundmounting diameter22.3 mmpositive tolerance of installation diameter0.4 mmmounting height27.5 mminstallation width60 mminstallation depth24.4 mm	height	60 mm
mounting diameter 22.3 mm positive tolerance of installation diameter 0.4 mm mounting height 27.5 mm installation width 60 mm installation depth 24.4 mm	width	60 mm
positive tolerance of installation diameter 0.4 mm mounting height 27.5 mm installation width 60 mm installation depth 24.4 mm	shape of the installation opening	round
mounting height 27.5 mm installation width 60 mm installation depth 24.4 mm	mounting diameter	22.3 mm
installation width 60 mm installation depth 24.4 mm	positive tolerance of installation diameter	0.4 mm
installation depth 24.4 mm	mounting height	27.5 mm
	installation width	60 mm
Certificates/ approvals	installation depth	24.4 mm
	Certificates/ approvals	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-1CD20-0AA0-Z Y10

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-1CD20-0AA0-Z Y10

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-1CD20-0AA0-Z Y10

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-1CD20-0AA0-Z Y10&lang=en

last modified:

1/27/2022 🖸