

# 3M<sup>TM</sup> Fabric Tape CN-3490

## Non-Woven Conductive

Data Sheet

October 2008

**Description** 3M<sup>TM</sup> Fabric Tape CN-3490 is a conductive, non-woven fabric and unique electrically conductive pressure-sensitive acrylic adhesive.

**Applications** CN-3490 tape is used for applications requiring excellent electrical conductivity from the substrate through the adhesive to the conductive backing. Common uses include grounding and EMI shielding equipment, components, shielded rooms, etc.

The unique and thin metallized backing offers the additional benefits of excellent flexibility and conformability, very light weight, and exceptional strength. The conductive backing also helps minimize the possibility of finger lacerations.

**Shielding Effectiveness** Many factors determine the true shielding effectiveness of a shielding tape, including type and thickness of foil adhesive type, intimacy of contact, smoothness of application surface, strength and frequency of the EMI signal, etc.

### Typical Properties

Technical information provided consists of typical product data and should not be used for specification purposes. Unless otherwise noted, all tests are performed at room temperature.

#### Physical

Property (Test Method) (ASTM D1000 unless noted)	Typical Value US units (metric)
Color	Grey
Adhesive	Conductive acrylic
Type of Backing	Copper/Nickel coated non-woven fabric
Total Thickness (backing plus adhesive)	2.4 mils (0,06 mm)
Liner Thickness	5.8 mils (0,14 mm)
Breaking Strength	35 lb/in (16 kgf/25 mm)
Adhesion Strength	30 oz/in (800 gf/25 mm)



# 3M™ Fabric Tape CN-3490

## Non-Woven Conductive

---

### Typical Properties

#### Electrical

Property (Test Method) (ASTM D1000 unless noted)	Typical Value US units (metric)
Electrical Resistance Through Adhesive <sup>1</sup>	0.05 ohms

<sup>1</sup> MIL-STD-202 Method 307 maintained at 5 psi (3,4 N/cm<sup>2</sup>) measured over in<sup>2</sup> surface area. Conductive particles in the adhesive provide the electrical path between the application substrate and the foil backing.

---

### Specifications

- Cu/Ni plated conductive non-woven fabric
- Conductive acrylic adhesive
- Supplied on a removable liner for easy handling and die cutting

---

### Shelf Life & Storage

This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (50°F/10°C to 80°F/27°C and 75% relative humidity).

---

### Availability

For availability, please contact your local distributor. Names and addresses are available from [3M.com/electrical](http://3M.com/electrical) [Where to Buy] or call 1-800-676-8381.

---

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

---

### Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

---

3M is a trademark of 3M Company.



#### Electrical Markets Division

6801 River Place Blvd.  
Austin, TX 78726-9000  
800 676 8381  
FAX 800 828 9329  
[www.3M.com/electrical/oem](http://www.3M.com/electrical/oem)

Please recycle.  
© 3M 2008 All rights reserved.  
78-8127-7047-3\_A