

UC-414






RoHS Compliant



uPCI 3+1xRS232+LPT Printer Port

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 4 port RS232
- PCI 3.0
- 64 Byte Tx and 64 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



UC-414: uPCI 3+1xRS232+LPT Printer Port

Description

Universal PCI providing four RS232 serial ports and one LPT port 3 industry standard 9 pin D RS232 ports on the bracket with a another 9 pin D RS232 port on a flylead. The 25pin D LPT port is also available by a flylead. Data transfer rates up to 115,200 baud rates and the 64 byte deep transmit and 64 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.Includes drivers for all Windows 32 bit and 64 bit Operating Systems, including Windows 7.


With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

popular programming languages. Further OS support on next page.

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows XP 32 bit 64 bit editions







ORDER Description uPCl 3+1xRS232+LPT Printer Port

Code UC-414

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com

UC-414

uPCI 3+1xRS232+LPT Printer Port

UC-414Full Specification

Port	Ports	4 x RS232
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	DB9 Connector 9 Pin Male and LPT port
Pin 2 RXD Pin 1 Pin 5 Pin 3 TXD	FIFO size	64 RX FIFO + 64 TX FIFO
Pin 4 DTR Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Im DSR Pin 7 RTS Pin 8 CTS Pin 9 R1	Cable	1 port RS232 on fly lead
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
\triangleright \diamond \diamond \diamond	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions
		Windows Server 2008 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions
PCI°		Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions
		Windows XP 32 bit 64 bit Editions
		DOS
	BUS	Plus Printer Port :
Approvals	Industry Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS EMC: CE TAA
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions
		Windows Server 2008 32 bit 64 bit editions
		Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions
		Windows XP 32 bit 64 bit editions
General	PCB Layers	4
	Power Consumption	300mA @ 5V, 60mA @ 12V
	Weight	0.098 kg
	Size	133l x 18w x 120h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	uPCI 3+1xRS232+LPT Printer Port
		1 port RS232 on fly lead
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

+44(0) 151 220 2500 | sales@brainboxes.com

Other PCI Cards: 1xRS232 | 2xRS232 | 4xRS232 | 8xRS232 | 1xRS422/485 | 2xRS422/485 | 4xRS422/485 Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial

www.brainboxes.com