

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
F1		REV. BY ECO 16-003733	11MAR2016	HC	WLS
F2		REV. BY ECO 18-012656	12AUG2018	HC	WLS
G		REVISED PER ECO-19-015171	08OCT2019	WLS	WLS
H		REVISED PER ECN-23-214009	23MAY2023	WLS	JS

RAW MATERIAL ACC. TO SPECIFICATION IEC 60335-1, GWEPT 750°C, WITHOUT FLAME.

	NATURAL	PA 6.6 V-0	141628-5
	BLACK	PA 6.6 THERMO-STABILIZED	141628-4
OBSOLETE	YELLOW	PA 6.6 94 V2	141628-3
	NATURAL	PA 6.6 94 V2	141628-2
OBSOLETE	NATURAL	PA 6.6 94 V1	141628-1
	FINISH	MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 29 JAN 2016

H.C. CANTERI

CHK 29 JAN 2016

W.L. STEFANI

APVD 29 JAN 2016

-

PRODUCT SPEC

108-37094

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

NAME

FASTON REC. HSG. .110 SERIES

SIZE

A3

CAGE CODE

-

DRAWING NO

C-141628

RESTRICTED TO

-

SCALE

4:1

SHEET

1

OF

1

REV

H

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±0,3
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±1°

MATERIAL

SEE TABLE

FINISH

-

1470-19 (3/13)