



Adjustable-length Twist lever for position switch 3SE51/52 Metal lever 100 mm long Stainless steel roller 19 mm

|  |  |
|--|--|
| <b>product brand name</b>                                | SIRIUS   |
| <b>product designation</b>                               | actuator for part-turn actuator  |
| <b>product type designation</b>                          | 3SE5   |
| <b>manufacturer's article number</b>                     |  |
| • of the supplied operating lever                        | <a href="#">3SE5000-0AA51</a>  |
| suitability for use safety switch                        | No   |
| <b>General technical data</b>                            |  |
| product function positive opening                        | No   |
| <b>shock resistance</b>                                  |  |
| • according to IEC 60068-2-27                            | 30g / 11 ms  |
| <b>vibration resistance</b>                              |  |
| • according to IEC 60068-2-6                             | 0.35 mm/5g   |
| mechanical service life (switching cycles) typical       | 15 000 000   |
| <b>reference code according to IEC 81346-2</b>           | T  |
| <b>active principle</b>                                  | mechanical   |
| <b>Substance Prohibitance (Date)</b>                     | 07/01/2006   |
| design of the interface for safety-related communication | without  |
| <b>Enclosure</b>   |  |
| <b>coating of the enclosure</b>                          | Other types  |
| <b>Drive Head</b>  |  |
| <b>design of the actuating element</b>                   | Adjustable twist lever, adjustable-length metal lever, high-grade steel roller 19 mm |
| <b>shape of the switch head</b>                          | roller   |
| <b>outer diameter of the switch head</b>                 | 19 mm  |
| <b>Communication/ Protocol</b>                           |  |
| <b>design of the interface</b>                           | without  |
| <b>Ambient conditions</b>                                |  |
| <b>ambient temperature</b>                               |  |
| • during operation                                       | -25 ... +85 °C   |
| • during storage   | -40 ... +90 °C   |
| <b>explosion protection category for dust</b>            | none   |
| <b>Installation/ mounting/ dimensions</b>                |  |
| <b>mounting position</b>                                 | any  |
| <b>fastening method</b>                                  | screw fixing   |
| <b>Certificates/ approvals</b>                           |  |
| <b>General Product Approval</b>                          |  |



[Confirmation](#)



[KC](#)



Declaration of Conformity

Test Certificates

other



EG-Konf.

[Type Test Certificates/Test Report](#)

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE5000-0AA51>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE5000-0AA51>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE5000-0AA51>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE5000-0AA51&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE5000-0AA51&lang=en)

last modified:

12/21/2020