## 12 INCHES LENGTH



Connector A 132113RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 142206 SMB Plug Right Angle Brass Gold + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|  | Connector A      |                      |  | Cable        |   |                             | Connector B   |                                     |  |
|--|------------------|----------------------|--|--------------|---|-----------------------------|---|-------------------------------------|--|
| Ра                                       | art #:           | 132113RP             |  | Part #:      | RG-58                                     | Part #:                     | 142206  |                                     |  |
| De                                       | escription:      | SMA PLUG RP RG58 500 |  | Description: | RG-58 - PE 0.196                          | Description:                | SMB R/A PLUG RG   | SMB R/A PLUG RG58 LMR195 500        |  |
| Ту                                       | /pe:             | SMA                  |  | Dielectric:  | PE  | Туре:                       | SMB   |                                     |  |
| Ge                                       | ender:           | Plug                 |  | Shielding:   | Braid                                     | Gender:                     | Plug  |                                     |  |
| Bo                                       | ody Type:        | Straight             |  | Diameter:    | 0.196                                     | Body Type:                  | Right Angle   |                                     |  |
| Co                                       | ontact Type:     | Crimp                |  | Impedance:   | 50 Ohm                                    | Contact Type:               | Solder  |                                     |  |
| Po                                       | olarity:         | Reverse              |  | Sheathing:   | None                                      | Polarity:                   | Standard  |                                     |  |
| Im                                       | npedance:        | 50 Ohm               |  | Testing:     | Continuity Hi-Pot                         | Impedance:                  | 50 Ohm  |                                     |  |
| Mc                                       | ounting:         | Cable                |  | Length:      | 12 Inches                                 | Mounting:                   | Cable   |                                     |  |
| Bo                                       | ody Material:    | Brass                |  |              |   | Body Material:              | Brass   |                                     |  |
| Bo                                       | ody Finish:      | Gold                 |  |              |   | Body Finish:                | Gold  |                                     |  |
| IP                                       | Rating:          | None                 |  |              |   | IP Rating:                  | None  |                                     |  |
| Co                                       | ontact Material: | Beryllium Copper     |  |              |   | Contact Material            | Beryllium Copper  |                                     |  |
| Co                                       | ontact Finish:   | Gold                 |  |              |   | Contact Finish:             | Gold  |                                     |  |
| Ma                                       | ax. Freq.:       | 12.4 GHz             |  |              |   | Max. Freq.:                 | 4 GHz   |                                     |  |
| Bo                                       | ooting:          | SMA Plug Straigh     | t RP   |              |   | Booting                     | SMB Plug Right Ang  | gle                                 |  |
|  |                  |                      |  |              |   | Clocking:                   | 0°  |                                     |  |
| Amphenol                                 |                  |                      | AND MUST NOT BE U<br>TAL TO CUSTOM CAE   | LE           | Title:<br>SMA-ST-PL-RP/SMB-RA-PL RG58 12I |                             | UNLESS SPECIFIED<br>TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2% |                                     |  |
|  |                  |                      | IN ANY FORM WITHOUT THE WRITTEN CONSENT OF<br>CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING |              |   |                             |   | ASSEMBLY:<br>CENTER LABEL IF LENGTH |  |
| <b>CONTROLLED DOCUMENT - DO NOT COPY</b> |                  |                      | ESTABLISHES AND AGREEMENT OF THE FOREGOING.  |              |   | Part No:<br>Q-6903U0008012I |   |                                     |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-6903U0008012I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL-RP/SMB-RA-PL RG58 12I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank