## **Potentiometers**



iductive plastic  ductive plastic  53 Series avail on composition	0.5  2.0  able with  2.25	150-5 meg  50-5 meg  rotary switc	±10%, ±20%  ±10%, ±20%	Linear Non-Linear Linear Non-Linear Non-Linear	15/16" dia.  1" dia.  1.156" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal  Plain, Slotted Flatted Knurled 1/4 " dia. Metal  Plain, Slotted 1/4" dia. Metal	Plain Locking 3/8" dia. Metal  Plain Locking 3/8" dia. Metal  Plain Locking Watertight 3/8 " dia. Metal	PC Solder lug Wire-wrap Solder lug
ductive plastic  53 Series avail on composition	2.0 lable with 2.25	50-5 meg rotary switc 50-5 meg	±10%, ±20%  hes.  ±10, ±20%	Linear Non-Linear	1" dia. 1.156" dia.	Flatted Knurled 1/4" dia. Metal  Plain, Slotted Flatted Knurled 1/4 " dia. Metal  Plain, Slotted Flatted Flatted 1/4" dia.	Locking 3/8" dia. Metal  Plain Locking 3/8" dia. Metal  Plain Locking Watertight 3/8 " dia.	Solder lug Wire-wrap
53 Series avail	lable with	rotary switc	hes. ±10, ±20%	Non-Linear Linear Non-Linear	1.156" dia.	Flatted Knurled 1/4 " dia. Metal  Plain, Slotted Flatted 1/4" dia.	Locking 3/8" dia. Metal  Plain Locking Watertight 3/8 " dia.	
on composition	2.25	50-5 meg	±10, ±20%	Non-Linear		Flatted 1/4" dia.	Locking Watertight 3/8 " dia.	Solder lug
·				Non-Linear		Flatted 1/4" dia.	Locking Watertight 3/8 " dia.	Solder lug
J Series availa	ble as Bri	idged-T, Brid	ged-H, L and S	Straight-T atten	uators.	!		<u> </u>
ductive plastic	2.0	50-5 meg	±10%, ±20%	Linear Non-Linear	1" dia.	Plain, Slotted Flatted Knurled	Plain Locking 3/8" dia.	Solder lug
200 Carias ava	فأريد واطوانا	h watani awit	ahaa 100,000	avala lifa		Metal	Metai	
	1	1		1		T		
ductive plastic	1.0	100-5 meg	±10, ±20%	Linear Non-Linear	5/8" dia.	Plain, Slotted Flatted Knurled 1/8" dia. Metal	Plain Locking 1/4" dia. Metal	Solder lug Wire wrap
381 Series ava	ailable wit	th rotary mor	nentary and alt	ternate action :	switches.	I.		
ductive plastic	2.0	50-5 meg	±10, ±20%	Linear Non-Linear	1" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
	ductive plastic  381 Series avaiductive plastic	ductive plastic 1.0  381 Series available wilductive plastic 2.0	ductive plastic 1.0 100-5 meg  381 Series available with rotary mor ductive plastic 2.0 50-5 meg	ductive plastic 1.0 100-5 meg ±10, ±20%	Non-Linear  Non-Linear  Non-Linear  Non-Linear  Non-Linear  Non-Linear  Non-Linear	ductive plastic  1.0 100-5 meg ±10, ±20% Linear Non-Linear  381 Series available with rotary momentary and alternate action switches.  ductive plastic  2.0 50-5 meg ±10, ±20% Linear Non-Linear  Non-Linear 1" dia.	380 Series available with rotary switches. 100,000 cycle life.  Iductive plastic 1.0 100-5 meg ±10, ±20% Linear Non-Linear S/8" dia. Plain, Slotted Flatted Knurled 1/8" dia. Metal  381 Series available with rotary momentary and alternate action switches.  Iductive plastic 2.0 50-5 meg ±10, ±20% Linear Non-Linear Non-Linear Non-Linear Non-Linear Relatted Knurled 1/4" dia. Metal	380 Series available with rotary switches. 100,000 cycle life.  Iductive plastic 1.0 100-5 meg ±10, ±20% Linear Non-Linear Non-Linear Non-Linear S/8" dia. Plain, Slotted Flatted Locking Knurled 1/4" dia. Metal Metal 1/8" dia. Metal Non-Linear

Clarostat provides Mil-spec products including, but not limited to the following units displayed in this catalog:

 Industrial	Board Washable	Wirewound	Trimmer	Resistor
Series 53(RV4) Series J(RV4) es 382(RV6), 392(RV6) G (RV6) and W(RV6)	Series 392 (RV6 & RV8) Series 382(RV6) G (RV6) W(RV6)	Series 43 (RA20) Series 58(RA30)	Series R(RJ11)	Series RW

*Milli*tary