

Jul.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD								
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C				
	_____	_____	_____	_____				
			APPLICABLE CABLE	φ8±0.5 mm				
SPECIFICATIONS								
ITEM	TEST METHOD		REQUIREMENTS	QT	AT			
CONSTRUCTION								
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X			
MARKING	CONFIRMED VISUALLY.			-	-			
ENVIRONMENTAL CHARACTERISTICS								
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.		NO HEAVY CORROSION.	X	-			
SEALING ⁽¹⁾	EXPOSED AT A DEPTH OF 1.8 m FOR 48h.		NO WATER PENETRATION INSIDE CONNECTOR.	X	-			
AIRTIGHTNESS ⁽¹⁾	APPLY AIR PRESSURE 18 kPa FOR 30s TO INSIDE CONNECTOR		NO AIR BUBBLES INSIDE CONNECTOR	X	-			
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE				
0								
REMARK			APPROVED	HY. KOBAYASHI	18.03.15			
NOTE(1) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.			CHECKED	HY. KOBAYASHI	18.03.15			
			DESIGNED	TH. KAMEYA	18.03.15			
			Unless otherwise specified, refer to IEC 60512.(JIS C 5402)			DRAWN	TH. KAMEYA	18.03.15
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-110598-31-00	
HRS	SPECIFICATION SHEET		PART NO.	JR13WCC-8 (31)				
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2049-1-31	△ 1/1			