




PWOK1.216.7W.A.007 Platinum sensor with wires For extended operating temperature range in class A

Benefits & Characteristics

- Capable of measuring in class A up to +600 °C •
- Increased long-term stability
- Alternative to wire-wound sensors
- Short-term applicable up to +750 °C

Illustration



Very stable characteristics curve

Very low hysteresis

Available with same dimensions as a wire-wound sensor

Technical Data

Operating temperature range:	-200 °C to +600 °C	
Nominal resistance:*	100 Ω at 0 °C	
Characteristics curve:*	3850 ppm/K	
Long-term stability:	< 0.04 % at 1000 h at maximal operating temperature	
Tolerance class:*	IEC 60751 F0.15	A (IST AG reference)
Connection:*	Pt-wire, Ø 0.2 mm (solderable, weldable, crimpable, brazeable), 7 mm long	
Dimensions:	2.4 x 1.4 x 0.45 / 0.8	
Tolerance (chip):	W ±0.2 mm, L ±0.2 mm, H ±0.1 mm, H2 ±0.3 mm	

Product Photo





Order InformationDescription:Item number:PW0K1.216.7W.A.007101700Additional DocumentsItem number:

Document name:

ATP_E

Application Note:



Innovative Sensor Technology IST AG, Stegrütistrasse 14, 9642 Ebnat-Kappel, Switzerland Phone: +41 71 992 01 00 | Fax: +41 71 992 01 99 | Email: info@ist-ag.com | www.ist-ag.com

All mechanical dimensions are valid at 25 °C ambient temperature, if not differently indicated • All data except the mechanical dimensions only have information purposes and are not to be understood as assured characteristics • Technical changes without previous announcement as well as mistakes reserved • The information on this data sheet was examined carefully and will be accepted as correct; No liability in case of mistakes • Load with extreme values during a longer period can affect the reliability • The material contained herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner • Typing errors and mistakes reserved • Product specifications are subject to change without notice • All rights reserved