



Main

| | |
|-------------------------------|----------------------------------|
| Range of Product | Harmony XAC |
| Product or Component Type | Contact block |
| Component name | XENT |
| Electrical circuit type | Control circuit Power circuit |
| Contact block application | Emergency stop push-button |
| Contact block type | Single |
| Type of operator | Spring return |
| Product Compatibility | XACD |
| Contacts type and composition | 3 NC |
| Contact operation | Slow-break |

Complementary

| | |
|--|--|
| Connections - terminals | Screw clamp terminals, 1 x 2.5 mm ² with or without cable end Screw clamp terminals, 2 x 1.5 mm ² with or without cable end |
| Mechanical durability | 3000000 cycles |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 400 V 3)IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 4 kV IEC 60947-1 |
| Short-circuit protection | 6 A fuse protection cartridge aM |
| Rated operational power in W | 3000 W AC-23B 400 V |
| Terminals description ISO n°1 | (31-32)NC (11-12)NC (21-22)NC |
| Net Weight | 0.09 lb(US) (0.04 kg) |

Environment

| | |
|---------------------------------------|---|
| Standards | EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 70 gn IEC 60068-2-27 |
| Overvoltage category | Class II IEC 61140 |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22466 - PUSHBUTTON, ACCESSORIES |
| Discount Schedule | CS2 |
| GTIN | 3389110609103 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.48 oz (42 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.42 in (3.6 cm) |
| Package 1 width | 2.09 in (5.3 cm) |
| Package 1 Length | 2.32 in (5.9 cm) |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 30 |
| Package 2 Weight | 3.22 lb(US) (1.462 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 5.91 in (15 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|