



### Main

Range of Product	9007
Series name	Heavy duty
Product or Component Type	Limit switch
Device short name	9007AW
Body type	Standard

### Complementary

Operator profile	Rotary head
Material	Metal
Body Material	Cast zinc
Operator material	Cast zinc
Movement of operating head	Rotary
Type of operator	Spring return lever arm Momentary to be ordered separately
Switch actuation	CCW
Electrical connection	1..2 screw-clamp terminals AWG 22...AWG 12)
Cable entry	Conduit entry 0.79 in (20 mm)
Contacts type and composition	NC-NO SPDT-DB
Contact form	Form Z
Contact operation	Snap action
Number of steps	1
Contacts material	Silver contacts
Positive opening	Without
Terminals description ISO n°1	(1-2)NC (3-4)NO
Minimum torque for tripping	2.75 lbf.in (0.31 N.m)
Tripping angle	2.5 °
Maximum displacement angle	30 °
[Ie] rated operational current	15 A 120 V AC, A600 NEMA rating designation
[Ithe] conventional enclosed thermal current	15 A
[Ui] rated insulation voltage	600 VUL 508 contact block
Width	2.69 in (68.33 mm)
Height	3.68 in (93.47 mm)
Depth	1.44 in (36.58 mm)
Net Weight	1.25 lb(US) (0.57 kg)
Product Certifications	UL listed file E42259 CCN NKCR CE CSA LR25490 class 3211 03

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

NEMA degree of protection	NEMA 1/2/4/12/13 Nema type 250
IP degree of protection	IP65 conforming to IEC 60529
Ambient Air Temperature for Operation	-60...185 °F (-51...85 °C)
Ambient Air Temperature for Storage	-60...185 °F (-51...85 °C)
Protective treatment	Epoxy powder coat
Mounting Location	Rear Front

## Ordering and shipping details

Category	21496-9007 AW PRECISION LIMIT SWITCHES
Discount Schedule	DS1
GTIN	785901288046
Nbr. of units in pkg.	1
Package weight(Lbs)	20.00 oz (566.991 g)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	17.78 in (45.161 cm)
Package 1 width	7.00 in (17.78 cm)
Package 1 Length	45.16 in (114.709 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------