







| Speci | fications | | - Notes | | Revision History | | | | | |
|--------------------------|-----------------|-------|-----------------------------|--------------|---------------------------|------------|-------------|------------|-------------|------------|
| Description | Value | Unit | | | Version | | Description | | Date | Approved |
| Resonant Frequency | 16,500 | (Hz) | 1) All dimensions are in mm | 1 | Released from Engineering | | | 10/21/2013 | J.S | |
| Resonant Impedance (Max) | 400 | (Ohm) | 2) All parts meet RoHS | | | | | | | |
| Max Input Voltage | 30 | (V) | | | | | | | | |
| Capacitance | 6,000 | (pF) | | | | | | | | |
| Plate Material | Stainless Steel | | | | | | | | | |
| Operating Temperature | -20 ~ +60 | °C | | | | | | | | |
| Storage Temperature | -20 ~ +70 | °C | | | | | | | | |
| | | | | | | | | | | |
| | | | | | Drawn by | Date | Checked by | Date | Approved by | Date |
| | | | | | A.B. | 10/21/2013 | C.E. | 10/21/2013 | J.S | 10/21/2013 |
| | | | DB UNLIMITED | Piezo Bender | | P13165- | | | -1 | |

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.