

## IRIS

~5° real spot beam optimized for CREE XM-L.  
Assembly with holder and installation tape.

### SPECIFICATION:

Dimensions	Ø 38.0 mm
Height	27.7 mm
Fastening	tape, pin, screw
ROHS compliant	yes ⓘ


### MATERIALS:

Component	Type	Material	Colour	Finish
IRIS	Single lens	PMMA	clear	
IRIS-XM-HLD	Holder	PC	black	
SPUTNIK-TAPE	Tape	Acrylic foam	black	



### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCA12104_IRIS	Single lens	378	126	42	9.0
» Box size: 480 x 280 x 300 mm					



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C12034	IRIS-XM-HLD	PC	black
2	F12075	IRIS	PMMA	clear

Tolerances if not otherwise shown  
According to DIN ISO 2768-1  
Linear measures:  
Up to 30mm class M, otherwise class C.  
According to DIN ISO 2768-2  
Form and position: class L

**LEDiL** Ledil Oy  
Joensuunkatu 13  
FIN 24100 SALO  
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE  
**FCA12104\_IRIS**









This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE	PART NUMBER
A4	FCA12104









SCALE	1:1	WEIGHT	19,5 g	SHEET	1/1
-------	-----	--------	--------	-------	-----

See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):

<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED XHP35 HD            FWHM / FWTM 10.0° / 22.0°            Efficiency 91 %            Peak intensity 17.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED XHP35 HI            FWHM / FWTM 7.0° / 16.0°            Efficiency 93 %            Peak intensity 33.8 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED XHP50.2            FWHM / FWTM 12.0° / 30.0°            Efficiency 88 %            Peak intensity 9.3 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED XM-L            FWHM / FWTM 9.0° / 19.0°            Efficiency 91 %            Peak intensity 19.2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		


### OPTICAL RESULTS (MEASURED):

<p><b>CREE</b> LED</p> <p>LED XM-L2            FWHM / FWTM 10.0° / 23.0°            Efficiency 86 %            Peak intensity 18.1 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NV4x144A            FWHM / FWTM 13.0° / 31.0°            Efficiency 89 %            Peak intensity 9.3 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NVSW3x9A            FWHM / FWTM 7.0° / 17.0°            Efficiency 85 %            Peak intensity 25.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSCONIQ P 3737 (2W version)            FWHM / FWTM 5.0° / 14.0°            Efficiency 91 %            Peak intensity 38.8 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		

#### OPTICAL RESULTS (SIMULATED):


##### CREE LED

LED J Series 5050B 6V K Class  
 FWHM / FWTM 10.0° / 26.0°  
 Efficiency 92 %  
 Peak intensity 13.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### CREE LED

LED J Series 5050C 6V E Class  
 FWHM / FWTM 10.0° / 25.0°  
 Efficiency 92 %  
 Peak intensity 14.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### CREE LED

LED XD16  
 FWHM / FWTM 6.0° / 14.0°  
 Efficiency 91 %  
 Peak intensity 47.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



##### CREE LED


LED XHP35.2 HD  
 FWHM / FWTM 8.0° / 20.0°  
 Efficiency 85 %  
 Peak intensity 21.1 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### OPTICAL RESULTS (SIMULATED):


#### CREE LED

LED XHP50.3 HD  
 FWHM / FWTM 13.0° / 28.0°  
 Efficiency 89 %  
 Peak intensity 10.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE LED

LED XHP50.3 HI  
 FWHM / FWTM 10.0° / 22.0°  
 Efficiency 96 %  
 Peak intensity 17 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE LED

LED XP-L HD  
 FWHM / FWTM 8.8° / 19.0°  
 Efficiency 93 %  
 Peak intensity 24.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:







#### LUMILEDS

LED LUXEON 5050 Round LES  
 FWHM / FWTM 10.0° / 27.0°  
 Efficiency 92 %  
 Peak intensity 13.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OPTICAL RESULTS (SIMULATED):

<p><b>LUMINUS</b></p> <p>LED SFT-40-WCS            FWHM / FWTM 6.0° / 14.0°            Efficiency 94 %            Peak intensity 46.6 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>LUMINUS</b></p> <p>LED SFT-70X-WCS            FWHM / FWTM 8.0° / 18.0°            Efficiency 94 %            Peak intensity 29.6 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>LUMINUS</b></p> <p>LED SST-70X-WCS            FWHM / FWTM 10.0° / 24.0°            Efficiency 92 %            Peak intensity 15.6 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED Duris S8            FWHM / FWTM 12.0° / 30.0°            Efficiency 92 %            Peak intensity 10.3 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)