

Industrial Ethernet Switch - FL SWITCH 4008T-2GT-4FX SM - 2891061

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Managed Ethernet switch with eight RJ45 ports at 10/100 Mbps, two RJ45 ports at 10/100/1000 Mbps and four SC-D fiber optic ports at 100 Mbps. Wide operating temperature of -40°C ... +75°C.

Product Description

FL SWITCH 4000 managed industrial Ethernet switches combine Gigabit interfaces with extensive network performance for the most demanding applications. Security features with complete IEEE redundancy (STP/RSTP/MST) and 15 ms recovery time extended ring redundancy optimize network uptime. Unique web customization provides a simplified user interface for today's applications and scalable functionality for future needs. A comprehensive mix of 10/100 Mbps and Gigabit fiber optic connections combine performance with installed cost savings.

Product Features

- Unique cleanup function hides unused configuration pages, reducing complexity, maintenance and startup times
- Secure web-based and SNMP-based management
- Extensive web diagnostics with configurable LED and remote alarm contacts
- Eight 10/100 Mbps RJ45 ports for device connections, two Gigabit RJ45 ports for network trunk lines and four 100 Mbps single mode fiber optic SC interfaces for remote connections
- -40 to 75°C ambient temperature



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 1750.0 g |
| Custom tariff number | 85176200 |
| Country of origin | Taiwan |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------|--------|
| Width | 66 mm |
| Height | 173 mm |

Industrial Ethernet Switch - FL SWITCH 4008T-2GT-4FX SM - 2891061

Technical data

Dimensions

| | |
|-------|--------|
| Depth | 140 mm |
|-------|--------|

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 75 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 57 kPa ... 108 kPa (up to 4850 m above mean sea level) |
| Air pressure (storage/transport) | 57 kPa ... 108 kPa (up to 4850 m above mean sea level) |

Interfaces

| | |
|---------------------------|-----------------------------------|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 8 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 MBit/s |
| Transmission length | 100 m |
| Interface 2 | Fiber optic interface |
| No. of ports | 4 (SC single mode) |
| Connection method | SC |
| Transmission physics | Single-mode fiberglass |
| Transmission speed | 100 MBit/s (full duplex) |
| Transmission length | 40 km |
| Interface 4 | Ethernet (RJ45) |
| No. of ports | 2 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100/1000 MBit/s |
| Transmission length | 100 m |

Function

| | |
|----------------------------------|--|
| Basic functions | Managed switch |
| Status and diagnostic indicators | LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port |

Network expansion parameters

| | |
|-----------------|--|
| Cascading depth | Network, linear, and star structure: any |
|-----------------|--|

Industrial Ethernet Switch - FL SWITCH 4008T-2GT-4FX SM - 2891061

Technical data

Network expansion parameters

| | |
|---|-------|
| Maximum conductor length (twisted pair) | 100 m |
|---|-------|

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC (redundant) |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 12 V DC ... 48 V DC |
| Typical current consumption | 488 mA (24 V DC) |
| Inrush surge current | 8 A (200 µs) |

General

| | |
|------------------|----------------------------|
| Mounting type | NS 35 (IEC 60715) DIN rail |
| Type AX | Block design |
| Net weight | 1300 g |
| Housing material | Aluminum |

Connection data

| | |
|---------------------------------------|---------------------------------------|
| Connection method | Pluggable COMBICON screw connections, |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Stripping length | 7 mm |

Standards and Regulations

| | |
|---------------------------------|--|
| Developed in acc. with standard | IEC 61000-6.2 |
| Test standard | IEC 61000-4-2 (ESD) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-3 (immunity to radiated interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-4 (burst) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-5 (surge) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-8 (immunity to magnetic fields) |
| Test result | Criterion A |

Industrial Ethernet Switch - FL SWITCH 4008T-2GT-4FX SM - 2891061

Technical data

Standards and Regulations

| | |
|----------------|--|
| Test standard | EN 55022 (emitted interference) |
| Test result | Class A |
| Test section | Supply voltage/functional earth ground 500 V 1 min. |
| Type of test | Shock in acc. with EN 60068-2-27/IEC 60068-2-27 |
| Test result | 30g, 11 ms half-sine shock pulse |
| Type of test | Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6 |
| Test result | 5g, 150 Hz, Criterion 3 |
| Type of test | Free fall in acc. with IEC 60068-2-32 |
| Test result | 1 m |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2:2005 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 19030117 |
| eCl@ss 5.1 | 19030117 |
| eCl@ss 6.0 | 19170106 |
| eCl@ss 7.0 | 19170106 |
| eCl@ss 8.0 | 19170106 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172901 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43201410 |

Approvals

Approvals

Industrial Ethernet Switch - FL SWITCH 4008T-2GT-4FX SM - 2891061

Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

UL Listed

cUL Listed

EAC

cULus Listed 
