## 48 INCHES LENGTH



Connector A 132113 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-58 Continuity/Hi-Pot Connector B 082-5378 N-Type Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| [  | Connector A       |                  |   | Cable  |                                  |                   | Connector B                        |  |  |
|--|-------------------|------------------|---|--|----------------------------------|-------------------|------------------------------------|--|--|
|  | Part #:           | 132113           |   | Part #:  | RG-58                            | Part #:           | 082-5378                           |  |  |
|  | Description:      | SMA PLUG RG58    | 3 LMR195 50O  | Description:   | RG-58 - PE 0.196                 | Description:      | N-Type BHD JK RG                   | 58 RG141 RG142 500                               |  |
|  | Туре:             | SMA              |   | Dielectric:  | PE                               | Туре:             | N-Type                             |  |  |
|  | Gender:           | Plug             |   | Shielding:   | Braid                            | Gender:           | Jack                               |  |  |
| 1 1  | Body Type:        | Straight         |   | Diameter:  | 0.196                            | Body Type:        | Straight                           |  |  |
| 1 1  | Contact Type:     | Solder           |   | Impedance:   | 50 Ohm                           | Contact Type:     | Solder                             |  |  |
|  | Polarity:         | Standard         |   | Sheathing:   | None                             | Polarity:         | Standard                           |  |  |
|  | Impedance:        | 50 Ohm           |   | Testing:   | esting: Continuity Hi-Pot Impeda |                   | 50 Ohm                             |  |  |
|  | Mounting:         | Cable            |   | Length:  | 48 Inches                        | Mounting:         | Bulkhead - Rear Mount              |  |  |
|  | Body Material:    | Brass            |   | _  |                                  | Body Material:    | Brass                              |  |  |
|  | Body Finish:      | Gold             |   |  |                                  | Body Finish:      | Nickel                             |  |  |
|  | IP Rating:        | None             |   |  |                                  | IP Rating:        | None                               |  |  |
|  | Contact Material: | Brass            |   |  |                                  | Contact Material: | Phosphor Bronze                    |  |  |
|  | Contact Finish:   | Gold             |   |  |                                  | Contact Finish:   | Gold                               |  |  |
|  | Max. Freq.:       | 12.4 GHz         |   |  |                                  | Max. Freq.:       | 11 GHz<br>N-Type Jack Straight BHD |  |  |
|  | Booting:          | SMA Plug Straigh | it  |  |                                  | Booting:          |                                    |  |  |
|  |                   |                  |   |  | Clocking:                        | 0°                |                                    |  |  |
| THIS DRAWING MAY CONTAIN                       |                   |                  |   | Title:   |                                  |                   | UNLESS SPECIFIED<br>TOLERANCE:     |  |  |
|  | Amphenol          |                  |   | TAL TO CUSTOM CABLE  |                                  | JK RG58 481       | 58 481                             |  |  |
| CUSTOM CABLE                                   |                   |                  |   | INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED<br>IN ANY FORM WITHOUT THE WRITTEN CONSENT OF |                                  |                   |                                    | over 18" +/- 2%<br>ASSEMBLY:                     |  |
| CONTROLLED DOCUMENT DO NOT CODY CUSTOM CABLE I |                   |                  | CUSTOM CABLE INC. ACCEPTA<br>ESTABLISHES AND AGREEMEN |  |                                  |                   |                                    | CENTER LABEL IF LENGTH<br>IS LESS THAN 12 INCHES |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 9/30/2023

Part Number: Q-3D01X0008048I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL/N-ST-JK RG58 48I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank