



- Specifications:
1. Insulation Resistance: 100MΩhms min. (Initial)
  2. Contact Resistance (Initial): 30mΩhms max at 100mA(max) 1KHz.
  3. Dielectric Withstand Voltage: AC 250V, 50 to 60Hz for 1 minute.
  4. Endurance: 5,000 Cycles 10 ~ 20 cycles per minute.
  5. Rated Voltage: 3.15 Volts DC
  6. Rated Current: 2.0 Amps DC
  7. Operating Temp: -25 to +85 deg. C.

Unless otherwise specified:  
Dimensions Tolerance on Decimals ±0.3

| No. | Description     | Material    | Finish      | Qty | Note    |
|-----|-----------------|-------------|-------------|-----|---------|
| 5   | Shield          | SPCC        | Nickel      | 1   | 40T     |
| 4   | Center Pin      | PBW         | Silver      | 1   | ∅0.65   |
| 3   | Shunt Terminal  | Brass       | Silver      | 1   | 40T     |
| 2   | Spring Contact  | Ti-Cu Alloy | Silver      | 1   | 30T     |
| 1   | Plastic Housing | Polyamide   | Black Color | 1   | UL94V-0 |



9615 SW Allen, Suite 103  
Beverton, OR 97005  
Phone: (503) 643-4899  
800-276-4899  
Fax: (503) 372-1266  
Website: www.cui.com

TITLE: ∅0.65 DC Power Jack w/ Shield, PCB Mount