

Data sheet | Item number: 221-942

Jumper; for conductor entry; 2-way; insulated; dark gray

www.wago.com/221-942



Color:

Data

Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated current	41 A

Physical data

Jumper assignment	1-2
-------------------	-----

Material Data

Note (material data)	Information on material specifications can be found here
Color	dark gray
Insulation material	Polyamide (PA66)
Weight of insulation material	0.28 g
Weight	2.7 g

Environmental requirements

Continuous operating temperature	-60 ... +105 °C
----------------------------------	-----------------

Commercial data

ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	5 pcs
Packaging type	bag
Country of origin	CN
GTIN	4055144067965
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



221-942 doc - Datei	docx 28.2 kB	Download
------------------------	-----------------	----------

221-942 X81 - Datei	xml 3.0 kB	Download
------------------------	---------------	----------

Additional Information

	pdf 2.2 MB	Download
--	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 221-942	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 221-942 Jumper; for conductor entry; 2-way; insulated; dark gray	URL	Download
--	-----	----------

Installation Notes

Commoning



Extending the N and PE (ground) distribution via jumper

Commoning

Subject to changes. Please also observe the further product documentation!



Insert the jumper without a locking function into open clamping units.

Commoning



Without a locking function:

The jumper without a locking function is plugged into the splicing connectors.

Commoning



Remove the jumper from open clamping units.

Subject to changes. Please also observe the further product documentation!