1-2199119-6 V ACTIVE

M.2 NGFF

TE Internal #: 1-2199119-6

M.2 Connectors, Height .126 in [3.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > M.2 Connectors > M.2 Connectors



Connector Height: 3.2 mm [.126 in]

Connector & Keying Code: M

Contact Mating Area Plating Material: Gold

PCB Contact Termination Area Plating Material Finish

PCB Contact Termination Area Plating Material

Contact Mating Area Plating Material

Contact Base Material

Connector System: Board-to-Board

Number of Positions: 67

All M.2 Connectors (29)

Features

Product Type Features		
Connector System	Board-to-Board	
Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Number of Rows	2	
PCB Mount Orientation	Right Angle	
Number of Positions	67	
Electrical Characteristics		
Operating Voltage	50 VAC	
Body Features		
Primary Product Color	Black	
Connector & Keying Code	M	
Contact Features		
	30 μin	

Matte

Gold

Gold Flash, Tin

Copper Alloy



Contact Current Rating (Max)	.5 A
------------------------------	------

Termination Features

Termination Method to Printed Circuit Board	Surface Mount
---	---------------

Mechanical Attachment

Connector Mounting Type	Board Mount

Housing Features

Housing Material	High Temperature Thermoplastic
Centerline (Pitch)	.5 mm[.02 in]

Dimensions

Connector Length	21.9 mm[.862 in]
Connector Width	8.7 mm[.343 in]
Connector Height	3.2 mm[.126 in]

Usage Conditions

Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]

Operation/Application

Circuit Application	Power	
	1 0 1 0 1	

Packaging Features

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series M.2 NGFF



Customers Also Bought























Documents

Product Drawings

M.2 0.5PITCH 3.2H KEY M 30U" AU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2199119-6_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2199119-6_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2199119-6_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1-1773702-1_NGFF_QRG-EN

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance Document

M.2 Connectors, Height .126 in [3.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF



English

Product Compliance Document

English