

# Han 10B-HMC-asg2-LB-M25



Part number	19 30 210 0291
Specification	Han 10B-HMC-asg2-LB-M25
HARTING eCatalogue	https://b2b.harting.com/19302100291

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HMC
Type of hood/housing	Surface mounted housing
Туре	High construction
Version	

Size	10 B
Version	Side entry
Cable entry	2x M25
Locking type	Single locking lever
Han-Easy Lock <sup>®</sup>	Yes
Field of application	Special hoods and housings for high mating cycles

## **Technical characteristics**

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

## Material properties

Material (hood/housing)	Aluminium die-cast
Page 1 / 2   Creation date 2022 OF 17   Diagon note that the date encoding here were taken as extracts from the online extellative. Diagon refer to	

Page 1 / 2 | Creation date 2023-06-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany Product data sheet 19 30 210 0291 Han 10B-HMC-asg2-LB-M25



## Material properties

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate (PC) Stainless steel
Colour (locking)	RAL 7037 (dust grey)
Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
ECHA SCIP number	16ca3004-52e6-46fa-bf13-9c1e1b30f813
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Naphthalene
California Proposition 65 substances Fire protection on railway vehicles	
	Naphthalene
Fire protection on railway vehicles	Naphthalene EN 45545-2 (2020-08) R22 (HL 1-3)
Fire protection on railway vehicles Requirement set with Hazard Levels	Naphthalene EN 45545-2 (2020-08) R22 (HL 1-3)
Fire protection on railway vehicles Requirement set with Hazard Levels Specifications and approvals	Naphthalene EN 45545-2 (2020-08) R22 (HL 1-3) R23 (HL 1-3)
Fire protection on railway vehicles Requirement set with Hazard Levels Specifications and approvals Approvals	Naphthalene EN 45545-2 (2020-08) R22 (HL 1-3) R23 (HL 1-3)

Packaging size	1
Net weight	371 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140127531
eCl@ss	27440202 Shell for industrial connectors

Page 2 / 2 | Creation date 2023-06-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany