

Display/Operation

Power indicator	no
-----------------	----

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
Min. operating current I _m	5 mA
Operating voltage U _b	10...55 VDC
Protection class	II
Rated insulation voltage U _i	250 V AC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Rated short circuit current	100 A
Ready delay t _v max.	10 ms
Residual current I _r max.	500 µA
Ripple max. (% of U _e)	15 %
Switching frequency	2500 Hz
Voltage drop static max.	5 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
IP rating	IP68

Functional safety

MTTF (40 °C)	610 a
--------------	-------

Interface

Switching output	Non-polarized normally open (NO)
------------------	----------------------------------

Material

Housing material	Stainless steel
Material sensing surface	PA 12


Mechanical data

Dimension	Ø 12 x 70 mm
Installation	for flush mounting
Size	M12x1

Range/Distance

Assured operating distance S _a	1.6 mm
Hysteresis H max. (% of S _r)	20.0 %
Rated operating distance S _n	2 mm
Real switching distance s _r	2 mm
Repeat accuracy max. (% of S _r)	5.0 %
Temperature drift max. (% of S _r)	10 %
Tolerance S _r	±10 %

Connector Drawings



Wiring Diagrams

