


HT06AB224JN Obsolete

HP LDD Indust X7R HT200C, Ceramic, 0.22 uF, 5%, 25 VDC, X7R, Commercial, High Temperature, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	7.62mm MAX
Н	7.62mm MAX
т	3.81mm MAX
S	5.08mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

General Information		
Series	HP LDD Indust X7R HT200C	
Style	Radial	
Description	Commercial, High Temperature	
Features	LDD High Temperature 200C	
RoHS	No	
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
Termination	Nickel	
AEC-Q200	No	

Specifications				
Capacitance	0.22 uF			
Capacitance Tolerance	5%			
Voltage DC	25 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	X7R			

Packaging Specifications

Packaging

Waffle, Tray

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.